

# LEDone

Projects:

Comments:

## 18W 4ft T8 LED Integrated Linear Tubes

### SPECIFICATIONS:

<b>WATTAGE:</b>	18W
<b>MODEL #:</b>	T84F-18W40KF-INTEGRATED (Frosted) T84F-18W50KF-INTEGRATED (Frosted) T84F-18W50KC-INTEGRATED (Clear)
<b>CERTIFICATIONS:</b>	ETL, FCC, CE, RoHS, DLC (Pending)
<b>LAMP SHAPE:</b>	T8-Tube
<b>VOLTAGE:</b>	AC100-277V
<b>POWER FACTOR:</b>	0.95
<b>FREQUENCY:</b>	50/60 Hz
<b>LUMENS EFFICACY:</b>	110LM
<b>LED TYPE:</b>	SMD5252
<b>KELVIN (CCT):</b>	4000/5000
<b>CRI:</b>	>80
<b>IP RATING:</b>	IP40
<b>BEAM ANGLE (DEGREE):</b>	120° Degrees
<b>BASE TYPE / CONNECTION:</b>	G13 (R17D/FA8 Optional)
<b>LENS:</b>	Frosted/Clear
<b>MATERIALS:</b>	Aluminum Allow and PC Cover
<b>LIFE SPAN (HOURS):</b>	50,000 Hours
<b>DIMMING COMPATIBLE:</b>	No
<b>LENGTH OF WARRANTY (YEARS):</b>	5 Years Standard
<b>PRODUCT LENGTH:</b>	1200mm ( 4ft)
<b>PRODUCT DIAMETER:</b>	26mm (1in)
<b>WORKING ENVIRONMENT:</b>	-20°C to 40°C (-4°F to 104°F)
<b>SUGGESTED REPLACEMENT FOR:</b>	32-40 Watt
<b>PERCENTAGE OF WATTAGE SAVED:</b>	75%



### Features:

Energy saving, environmental protection, low carbon lighting. No mercury and lead contamination, 100% recyclable. No infrared and ultraviolet radiation, conducive to health. No fluorescence blinking, super stable and long service life.

### Applications:

Houses, offices, exhibitions, meeting rooms, hotels, restaurants, schools, factories, hospitals, workshops, storages, roads, streets, etc.

