

**LED VALUE PAR LAMPS**  
PAR20, PAR30, PAR38  
Non-Dimming Value Series



7W



10W



13W



**PRODUCT DESCRIPTION:**

MaxLite's energy-efficient LED VALUE PAR lamps offer 7, 10 and 13 watt LED replacements for 50-, 65-, and 90- incandescent lamps to significantly reduce your carbon footprint while maintaining a very high quality of light. Available in the PAR20, PAR30, and PAR38 sizes, Maxlite's lineup has industry leading light output, making it ideal for architectural and wall wash lighting in track, recessed and decorative lighting fixtures in retail, high-end residential and office environments. The LED Lamps produce a strong center beam candle power that provides bright and crisp lighting to showcase artwork and products.

**FEATURES:**

- 7W PAR20, 425 lumens, replaces 50W Inc.
- 10W PAR30, 750 lumens, replaces 65W Inc.
- 13W PAR38, 1,000 lumens, replaces 90W Inc.
- Beam angles: 40 available
- Available in 3000K & 5000K
- Voltage: 120V
- Frequency: 60Hz
- CRI: ≥82
- Instant on (no warm up time)
- Base: E26 (medium)
- UV and IR free
- Operating temperature range: - 4° to 104°F
- Power Factor: 0.98
- Ideal for use indoor
- Not for use in enclosed luminaires
- One year warranty
- 11,000 hour life at L70 standards

**APPLICATIONS:**

- Retail
- Hospitality
- Residential
- Restaurant
- Outdoor architectural/spot lighting

MODEL SELECTION (Full list of order codes on pg. 3)		Typical order example: 7P20NDV30FL	
	NDV		FL
FAMILY	DIMMABILITY	COLOR TEMPERATURE (CCT)	BEAM ANGLE
<b>7P20 =</b> 7 watts, PAR20 <b>10P30 =</b> 10 watts, PAR30 <b>13P38 =</b> 13 watts, PAR38	<b>NDV =</b> Non-Dimmable Value	<b>30 =</b> 3000K <b>50 =</b> 5000K	<b>FL =</b> Flood 40°

**SPECIFICATIONS:**

		PAR20	PAR30	PAR38
ITEM	SPECIFICATION	7 WATTS	10 WATTS	13 WATTS
<b>GENERAL PERFORMANCE</b>	Color Temperature	3000K, 5000K	3000K, 5000K	3000K, 5000K
	Lumens Delivered (lm)	425	750	1000
	Efficacy (lm/w)	60	75	76
	Equivalency	50W	65W	90W
	CRI	≥82		
	Lumen Maintenance (L70)	11,000 hours		
<b>ELECTRICAL</b>	Power Factor	≥0.98		
	Input Voltage	120V		
<b>PHYSICAL</b>	Operating Temperature	-4° F to 104° F		
<b>APPLICATION</b>	Environment	Damp		
	Certification	UL Listed		
	Warranty	1 Year		

**ORDERING (FLOOD MODELS):**

ORDER CODE	MODEL	WATTAGE	DELIVERED LUMENS	EFFICACY (lm/W)	INCANDESCENT EQUIVALENCY	BEAM ANGLE	CRI	CCT (K)	DIMENSION (MOL" X W")
<b>PAR20</b>									
102646	7P20NDV30FL	7W	425	60	50W Inc.	40°	82	3000K	4.16" x 2.48"
102647	7P20NDV50FL							5000K	
<b>PAR30</b>									
102648	10P30NDV30FL	10W	750	75	65W Inc.	40°	82	3000K	4.56" x 3.74"
102649	10P30NDV50FL							5000K	
<b>PAR38</b>									
102650	13P38NDV30FL	13W	1000	76	90W Inc.	40°	82	3000K	5.23" x 4.72"
102651	13P38NDV50FL							5000K	