

LED PLL
PLUG & PLAY COATED GLASS



PRODUCT DESCRIPTION:

The ballast-compatible PLL Lamp is the fast and simple way to upgrade downlights and commercial luminaires to the energy-saving benefits of LED. This plug-and-play replacement lamp operates off the existing instant or programmed start fixture ballast – no rewiring required! Designed as a seamless replacement for 40-watt CFL tubes, the LED PLL lamp consumes 50 percent less energy and lasts twice as long as its fluorescent counterpart.

FEATURES:

- Wattage: 13W
- Lumens: 2000
- CCT: 3500K, 4000K and 5000K
- Power factor: ≥ 0.90
- Type-A (ballast compatible)
- Suitable for enclosed fixtures
- 5 year warranty
- 2G11 Base
- UL Listed
- Coated glass construction

WARRANTY:

5-year standard warranty
(further details available at www.maxlite.com/warranties)
Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact MaxLite for details.

4FT MODEL SELECTION (Full list of order codes on pg. 3)		Typical order example: 13PLLaxx-CG	
13W	PLLA		
WATTAGE	FAMILY	CCT/ BASE	
13= 13 Watts	PLLA= PLL UL TYPE-A	30-CG= 3000K, Coated Glass, .2G11 35-CG= 3500K, Coated Glass, .2G11 40-CG= 4000K, Coated Glass, .2G11 50-CG= 5000K, Coated Glass, .2G11	

SPECIFICATIONS:

SPECIFICATIONS:		13PLLAXX-CG			
ITEM	SPECIFICATION	DETAILS			
GENERAL PERFORMANCE	Bare Lamp Wattage (W)	13W			
	Lumens Delivered* (lm)	2050 lm	2050 lm	2100 lm	2100 lm
	Color Temperature (CCT)	3000K	3500K	4000K	5000K
	Efficacy (lm/W)	124 lm/W	127 lm/W	127 lm/W	127 lm/W
	CRI	≥80			
	Lumen Maintenance (L70)	50,000 hours			
ELECTRICAL	Power Factor	≥ 0.90			
PHYSICAL	Operating Temperature	-4°F - 104°F			
CERTIFICATION	Certification	cULus Listed, FCC			
	Material Usage	RoHS compliant, no mercury			
	Environment	Dry, Damp			
	Warranty	5 Years			

* Operating with normal ballast factor (.88) ballast

ORDERING:

ORDER CODE	MODEL	CCT	AVERAGE SYSTEM WATTS		INITIAL LUMENS
			BARE LAMP WATTAGE	SYSTEMS WATTAGE	LUMENS
103366	13PLLA30-CG	3000K	13	22	2050
14100784	13PLLA35-CG	3500K	13	22	2050
14100785	13PLLA40-CG	4000K	13	22	2100
103285	13PLLA50-CG	5000K	13	22	2100

* Lumens and watts will vary by ballast and fixture

COMPATIBLE BALLAST:

13PLLAXX-CG				OK	Compatible	IS	Instant Start
				NO	Not compatible	PS	Programmed Start
				NA	Not required	NS	Noise
NO.	Brand	Model No.	Ballast Type	Compatible Status			
				Ballast work on 120-277V			
				1 lamp	2 lamps	3 lamps	4 lamps
1	Philips-Advance	ICN-2TTP40-SC	IS	OK	OK	NA	NA
2	Philips-Advance	ICF-2S42-M2-LD	PS	Only 120V	OK	NA	NA
3	Sylvania	QTP 2x26/32/42CF/UNV DM	PS	NO	OK	NA	NA
4	Sylvania	QHE 2x40DL/UNV ISN-SC	IS	OK	OK	NA	NA
5	Universal	C242UNVME	PS	OK	OK	NA	NA

Specifications are subject to change without notice.