

LEDone

—Distribution Inc—

: require general area or directional lighting, such as track lighting, recessed ceiling lights, retail display lighting or general household light fixtures.

FEATURES:

- Energy efficient, up to 80% less energy than halogen alternatives
- Durable
- Shatter resistant
- Solid state lighting technology the reduces lighting service and maintenance due to robust lighting design

DIMENSIONS:

BR40 E26 Bulb 17W Spec

BR40-90WE-17WD27K

BR40-90WE-17WD50K



SPECIFICATIONS:

| SPECIFICATION | Details | Details |
|-----------------------|-------------------------------------|-------------------------------------|
| Model | BR40-90WE-17WD27K | BR40-90WE-17WD50K |
| Input Wattage (W) | 17W | 17W |
| Lumens Delivered (LM) | 1,260LM | 1,260LM |
| Efficacy (LM/W) | 70LM/W | 74.1LM/W |
| CRI | 81 | 83 |
| Lifespan | 25,000 hours | 25,000 hours |
| Color Temperature | 2,700K | 5,000K |
| Wattage Equivalent | 90W | 90W |
| Dimmable | Yes | Yes |
| IP Rating | Damp Location | Damp Location |
| Beam Angle | 100 | 100 |
| Input Voltage | AC120V | AC120V |
| Power Factor | 0.9 | 0.9 |
| Housing | Aluminum | Aluminum |
| Lens | Frosted/Clear | Frosted/Clear |
| Mounting | E26 | E26 |
| Size | 6.50" x 5.12" | 6.50" x 5.12" |
| Certification | ES, UL, FCC, CE, RoHS, TUV, ISO9001 | ES, UL, FCC, CE, RoHS, TUV, ISO9001 |
| Operating Temperature | -20°C to 50°C (-4°F to 122°F) | -20°C to 50°C (-4°F to 122°F) |
| Environment | Indoor | Indoor |
| Warranty | 3 years limited | 3 years limited |

