

PRODUCT DESCRIPTION:

T8 linear tube retrofits are usually but not specifically used in commercial buildings such as hotels, conference rooms, schools, supermarkets, factory, parking garages, hospitals, airport, metro stations, bus stations, office buildings and any other sites where request long-time and hi-output lighting.

FEATURES:

- Input voltage is AC110V-277V
- Low thermal decay
- Low maintenance
- No mercury, lead-free
- No UV

COMPATIBLE BALLAST LIST:

- [For compatible ballasts, please check on the website under the Tube section > Plug & Play LED Glass Shatterproof > Ballast List](#)

Plug & Play Glass Tube 2FT 8.5W Spec

L1
L1



SPECIFICATIONS:

SPECIFICATION	Details	
Model	LOD-GDMT82F-8.5W40KF	LOD-GDMT82F-8.5W50KF
Input Wattage (W)	8.5W	8.5W
Lumens Delivered (LM)	1,150LM	1,150LM
Efficacy (LM/W)	136LM/W	136LM/W
CRI	80	80
Lifespan	50,000 hours	50,000 hours
Color Temperature	4,000K	5,000K
Wattage Equivalent	15W – 20W	15W – 20W
Dimmable	No	No
IP Rating	IP40	IP40
Beam Angle	270	270
Input Voltage	AC110-277V	AC110-277V
Power Factor	0.9	0.9
Housing	Glass	Glass
Lens	Frosted	Frosted
Mounting	G13	G13
Size	24"	24"
THD	10%	10%
Certification	DLC, ETL, FCC, CE RoHS, TUV, ISO9001	DLC, ETL, FCC, CE RoHS, TUV, ISO9001
Operating Temperature	-20°C to 50°C (-4°F to 122°F)	-20°C to 50°C (-4°F to 122°F)
Environment	Indoor	Indoor
Warranty	5 years limited	5 years limited

