




DIMENSIONS:



H 5" x W 5" x D 2"

DLS4-27K DLS4-30K
DLS4-41K DLS4-50K

LED Disc Downlight 4"

Universal surface mount
Fits most J-boxes & 5"/6" recessed housings
New direct A/C technology does not require an LED driver, contributes to longer life and generates less heat.
Rated for wet location.
Saves up to \$452.22
Last up to 30 years

ELECTRICAL SPECIFICATIONS:

- Working voltage: 120V AC
- Watts: 9W
- CRI: 90
- Power factor: 90% +

LIGHTING SPECIFICATIONS:

- Fully dimmable
- Lumens: 600
- Beam angle: 120°
- LED: Epistar —35,000 hour design life
- Lens: Translucent acrylic
- Color temperature: 2700K and 3000K (Warm white), 4100K (natural white), 5000K Daylight

CERTIFICATIONS: UL listed, Energy Star-rated



Recessed Mounting



Surface Mounting

MODEL	DIAMETER	WATTS	VOLTAGE	LUMENS	COLOR TEMP
DLS4-27K	4"	9W	120V AC	550~600	WW 2700K
DLS4-30K	4"	9W	120V AC	550~600	WW 3000K
DLS4-41K	4"	9W	120V AC	550~600	NW 4100K
DLS4-50K	4"	9W	120V AC	550~600	DL 5000K

HOUSING SPECIFICATIONS:

- Finish: White powder coat
- Housing: Spun aluminum
- Trim ring: Integrated spun aluminum white powder coat finish
- Gasket: Neoprene foam gasket
- Suitable for damp locations
- Maximum ambient 4°C (104°F)
- Suitable for use in IC Rated recessed housings

