EZRXTEU Compact LED Exit Sign

Project:	
Type:	
Catalog #:	



STANDARD









ILLUMINATION

• Ultra bright, energy efficient, long life Red or Green LED.

ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 1.2V Long life, maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- EZ-snap mounting canopy included for top or end mount.
- Universal K/O pattern on back plate for wall mount.


HOUSING

- Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.
- Aesthetically pleasing, curved face, rounded corner design.
- EZ snap-out chevron directional indicators.

WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery pro rated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (0°C 50°C).

DIMENSIONS



ORDERING INFORMATION

Sample Part Number: EZRXTEU-1-R-W-EM

MODEL	No. of FACES		LETTER COLOR		HOUSING COLOR		BATTERY	
EZRXTEU	1	Single Face	R	Red	W	White	Blank	AC Only
	2	Universal Single/ Double Face	G	Green	В	Black	EM	Battery Backup

EZRXTEU Compact LED Exit Sign

Project:	
Type:	
Catalog #:	

ELECTRICAL INFORMATION

CATALOG NUMBER	INPUT WATTS (W)		INPUT AMPS (A)	
	120V	277V	120V	277V
EZRXTEU-RED/GREEN/EM	0.8	0.8	0.09	0.09