




FL-SH3

FLD2-42W-50K-D-KN
FLD2-42W-30K-D-KN

DIMENSIONS:

8"(H) x 4-1/2"(W) x 6-1/4"(D)



LED BULLET FLOOD LIGHTS WITH KNUCKLE

Ideal for general site lighting, alleys, loading docks, doorway, path-way and parking areas. Great for use with motion sensors and other instant on/off controls.

ELECTRICAL SPECIFICATIONS:

- Voltage: 120-277VAC 50/60Hz
- Wattage: 42W
- Power factor: >0.9
- Efficacy: 123LM/W

HOUSING SPECIFICATIONS:

- Die-cast aluminum with powder coat finish (Bronze)
- Cord type: 18" SJTW 18/3 AWG cable
- Operating temperature: -40°F ~ 104°F
- Maintenance free
- High light transmittance, anti-UV & fire resistant PC
- Westgate's powerful bullets
- Mounting: 1/2" NTP knuckle
- Lifespan: 70,000 Hrs.
- IP rating: IP65, Wet Locations

ACCESSORIES:

MODEL	DESCRIPTION
FL-SH3	Polycarbonate shroud (Bronze) fits for FLD2-42W

LIGHTING SPECIFICATIONS:

- LED: Philips LUMILEDs
- Total lumens: 5200LM
- Color temperature: 5000K/3000K
- Color rendering index: >80
- Beam angle: 60°

WARRANTY: 7 years

CERTIFICATIONS: UL, DLC



Rev. 2021-01-27

