

JOB NAME:	
DATE:	



#### **DIMENSIONS:**



# **LED FLUSH MOUNT SURFACE FIXTURE (10")**

The LED Flush Mount Surface Fixture is a low profile downlight intended for ceiling or wall mount applications. Driver on Board (DOB) technology, with no driver or transformer needed. These flush mount ceiling lights mount directly to a 4" deep dish junction box. provides general LED illumination in residential and light commercial applications.

#### **FEATURES:**

- Driver on Board Technology provides a 120V alternating current source and eliminates the need for traditional LED driver.
- Quick and easy to install on standard junction box, wall or ceiling mount with mounting plate
- Die-cat aluminum housing, high transmittance lens allowing for smooth, comfortable light pattern

## **ELECTRICAL SPECIFICATIONS:**

Voltage: 120V ACWattage: 17WLumens: 950LM

Color Temperatures: 3000K and 5000K
Maximum Ambient Temperature: 104°F

· CRI: 90+

• Power Factor: 0.95

MODEL	WATTS	VOLTS	LUMENS	COLOR TEMP
FML-S10-17W-30K	17W	120V	950LM	3000K
FML-S10-17W-50K	17W	120V	950LM	5000K

## **LIGHTING SPECIFICATIONS:**

- Dimmable down to 10% using an approved dimmer
- LED: Epistar
- · Life span: 50,000 hours
- Suitable for Damp Locations when gasket

#### HOUSING SPECIFICATIONS:

- Housing: Die-cast aluminum
- · Finish: Powder coated white
- Diffuser: Matte white polycarbonate
- Gasket: Close cell Neoprene foam gasket
- · Optics: White translucent acrylic lens

**WARRANTY:** 

5 years

## **CERTIFICATIONS:**









