

FEATURES & SPECIFICATIONS

Great Performance Strip Fixture - now available with Lens. This LED offering is perfect for so many applications. Designed economically yet with balance and sleek aesthetics. This fixture is perfect for: Retail, Industrial, Back House applications as well as the perfect solution for Mezzanine low ceiling installations where a wide distribution light pattern is needed. 5 year factory warranty.

MOUNTING

Surface mount, chain hung, double stem.

TYPICAL OPTIONS AND ACCESSORIES

Whips, wireguards, Emergency battery backup (IOTA ILB-CP10HE), or contact factory for more details.

FSF Series

LED Medium Body Strip with Lens



SIZE*

W x L x H in inches

2ft: 4.25W x 24.00L x 3.25H 4ft: 4.25W x 48.00L x 3.25H 8ft: 4.25W x 96.00L x 3.25H

*All dimensions are inches. Speci ications subject to change without notice.

Example: FSF24LFRZ33W3300LDMV40K



2 ft - STANDARD

FR 24L Z33W3300L **FSF DMV** 40K Lens Wattage and Lumen Length **Series Driver** Kelvin Temperature 14 System Watts, 30K 3000K **DMV** 0-10V Dimming **FSF** FR Frosted Lens J14W1400L 1400 Delivered Lumens 35K 3500K Medium Body Strip J18W1800L 18 System Watts, 40K 4000K 1800 Delivered Lumens **SMFSF** 5000K 50K 28 System Watts, Z28W2800L Medium Body Strip 2800 Delivered Lumens with **Options** 33 System Watts, Z33W3300L Microware Sensor 3300 Delivered Lumens 6 ft. 3 wire 18 gauge whip WP10 6 ft. 4 wire 18 gauge whip

EM10HE 10w Emergency battery backup

MDT4 Occupancy Sensor

*Consult factory for more options

Saylite

2055 Luna Rd. Suite 142 Carrollton, TX 75006 Phone: 972-247-3171 Fax: 972-247-0200 www.saylite.com email: sales@saylite.com

Catalog Number:	
Notes:	



Texas Fluorescents

Reinvented



SS-Embedded Sensor

FSF Series

LED Medium Body Strip with Lens



4 ft - STANDARD

Example: FSFFR48LJ31W3100LDMV40K

FSF	FR	48L	J31'	W3100L		DMV	40	K
			***			D .		
Series	Lens	Length	Wattag	e and Lumen		Driver	Kelvin Tei	nperature
FSF	FR Frosted Lens	48 L 48"	J28W2800L	28 System Watts, 2800 Delivered Lumens	DMV	0-10V Dimming	30K 35K	3000K 3500K
Medium Body Strip SMFSF			J31W3100L	31 System Watts, 3100 Delivered Lumens			40K	4000K 5000K
Medium Body Strip			Z48W4800L	48 System Watts, 4800 Delivered Lumens			50K	
with Microware Sensor			Z57W5700L	57 System Watts, 5700 Delivered Lumens			WP	Options 6 ft. 3 wire 18 gauge
SSFSF			Z62W6200L	62 System Watts, 6200 Delivered Lumens				6 ft. 4 wire 18 gauge
Medium Body Strip with							EM10	10w Emergency batte backup
Embedded On/Off Sensor							EM12	12w Emergency batte backup
							MDT4	Occupancy Sensor

8 ft - STANDARD

<u>FSF</u>	FR	96L	J48W	74800L		DMV	40	K
Series	Lens	Length	Wattage a	and Lumen		Driver	Kelvin Te	mperature
FSF	FR Frosted Lens	96L 96"	J48W4800L	48 System Watts, 4800 Delivered Lumens	DMV	0-10V Dimming	30K 35K	3000K 3500K
Medium Body Strip SMFSF			J57W5700L	57 System Watts, 5700 Delivered Lumens			40K 50K	4000K 5000K
Medium Body Strip with			J61W6100L	61 System Watts, 6100 Delivered Lumens				Options
Microware Sensor			J62W6600L	62 System Watts, 6600 Delivered Lumens			WP	6 ft. 3 wire 18 gauge whip
SSFSF Medium Body Strip			Z97W9700L	97 System Watts, 9700 Delivered Lumens			WP10	6 ft. 4 wire 18 gauge whip
with			Z114W11400L	114 System Watts, 11400 Delivered Lumens			EM10	10w Emergency battery backup
Embedded On/Off Sensor			Z124W12400L	124 System Watts, 12400 Delivered Lumens			EM12	12w Emergency battery backup
							MDT4	Occupancy Sensor

*Consult factory for more options

Saylite

2055 Luna Rd. Suite 142 Carrollton, TX 75006 Phone: 972-247-3171 Fax: 972-247-0200 www.saylite.com email: sales@saylite.com

Catalog Number:	
Notes:	