

GSX SERIES Outdoor Lighting

GSX-SRFC-80-150W-50K
POWER-ADJUSTABLE SURFACE-MOUNT CANOPY LIGHT

WESTGATE
THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!



Selection:




Ideal for airport, auto dealership, corporate and office, education, government, healthcare, industrial and warehouse, municipal, parking, gas station and convenience stores, recreation and public venues, restaurants and hospitality, retail and grocery.

Customer Name: _____

Project Name: _____

Note: _____

Type: _____



16" (W) X 16" (H) X 3 1/2" (D)

Features

- ADC12 Aluminum Alloy, Outdoor Powder Coated
- Optical Lens: High Transmittance PC, Anti-UV & Fire Resistant
- 7-Year Warranty
- Multi-Power: Selectable Switch is on the side of the fixture

Technical Specifications

Electrical:

- Voltage: 120~277V AC, 50/60Hz
- Wattage: 80W/ 100W/ 120W/ 150W
- Power Factor: 0.95
- Efficacy: 140LM/W

Mechanical:

- ADC12 Aluminum Alloy, Outdoor Powder Coated
- 3/4" NPT threaded hub on the top allows stem mounting
- Mounting: Surface Mounting
- Programmable Bi-Level Motion Sensor & Emergency Backup Options
- Operating Temperature: -40°F~104°F
- IP Rating: IP65, Suitable for wet locations

Lighting:

- Dimming: 0-10V dimming
- LED: Philips Lumileds LEDs
- Optical Lens: High Transmittance PC, Anti-UV & Fire Resistant
- Multi-Power: Selectable Switch is on the side of the fixture
- Total Lumens: 21000LM Max.
- Color Temperature: 5000K
- Color Rendering index: >70
- Beam Angle: 100°X100°
- Lifespan: 70000 Hrs.

Applications:



- Ideal for airport, auto dealership, corporate and office, education, government, healthcare, industrial and warehouse, municipal, parking, gas station and convenience stores, recreation and public venues, restaurants and hospitality, retail and grocery.




Phone: (877) 805-2252 | Fax: (877) 805-2252
www.westgatemfg.com | www.westgatecontrols.co



Photometrics: GSX-SRFC-80-150W-50K




BUD Rating: B4-U2-G2



Area 75'x 75' Mounting Height: 9'

Other Views:



Side View



Front View



Back View

Performance Table: GSX-SRFC-80-150W-50K

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
GSX-SRFC-80-150W-50K	80W 100W 120W 150W	120-277V	11200LM 14000LM 16800LM 21000LM	5000K	B4-U2-G2	140

Sample Ordering

Model Surface Mount Min. Watt Max. Watt Color Temp.

GSX - SRFC - 80 - 150W - 50K

Factory-Installed Options

Blank = No Option

OPT-EM-HB2EXT = Emergency Battery Backup Option, mounts on top of the fixture

OPT-3PDR-52 = Bi-Level Motion Sensor Option, Remote Capable, Mounts Internal

WEC-3RC = Remote Control

FACTORY-INSTALLED OPTIONS:



OPT-EM-HB2EXT



OPT-3PDR-52



WEC-3RC

Example:

1. GSX-SRFC-80-150W-50K

(For GSX 150W 5000K MP fixture 120V-277V)

2. GSX-SRFC-80-150W-50K

(For GSX 150W 5000K MP fixture 120V-277V)

OPT-EM-HB2EXT

(For Emergency Battery Backup Option, Mounts on Top of the Fixture)

