



GZ-S8-32K
Single contact
bayonet based



GZ-JC-18L-32K
Fits standard GX 5.3
bi-pin low voltage
sockets 3W



GZ-G4-9L-32L



GZ-JC-WP-3W-32K



GZ-G9-3W-32K
GZ-G9-3W-55K



GZ-S8-32K / GZ-JC-18L-32K
GZ-G4-9L-32K / GZ-JC-WP-3W-32K
GZ-G9-3W-32K / GZ-G9-3W-55K

GZ

Replace existing halogen or incandescent lamps.
 Increase life expectancy 15 to 20 times over halogen.
 Ideal for low voltage landscape fixtures.

ELECTRICAL SPECIFICATIONS:

- Operating Voltage: 12 Volts AC
- Wattage: 1.5W / 1.4W / 3W

LIGHTING SPECIFICATIONS:

- Lumens: 70lm / 120lm / 180lm / 250lm
- CRI: >82
- Minimum starting temperature: -4°F (-20°C)
- Efficiency 60 + lumens per watt

WARRANTY:

- Five-year warranty

MODEL NO	LAMP	WATTS	LUMENS	VOLTAGE	COLOR
GZ-S8-32K	LED	1.4W	70	12V	WW3200K
GZ-JC-18L-32K	LED	3W	250	12V AC/DC	WW3200K
GZ-G4-9L-32L	LED	2W	120	12V	WW3200K
GZ-JC-WP-3W-32K	LED	3W	180	12V AC/DC	WW3200K
GZ-G9-3W-32K	LED	3W	220	100V-240V	WW 3200K
GZ-G9-3W-55K	LED	3W	250	100V-240V	DL 5500K

SPECIAL FEATURES:

- Improve efficiency by over 400%
- Save money by reducing transformer and wire size
- Reduce maintenance cost by 500%
- Wet Location

