

ROUND PENDANT LED HIGH BAY
HP Gen. 2 SERIES



PRODUCT DESCRIPTION:



The Round Pendant LED High Bay blends high performance with a premium aesthetic that is well suited to many industrial and commercial applications, including retail and big box stores, auto showrooms, gymnasiums, warehouses and manufacturing facilities. The high bay features cutting-edge optics that deliver exceptional efficacy up to 158 lm/W with minimal glare. The high bay also features a high transmission polycarbonate diffuser, a profile as low as 5", integrated sensor design, and innovative patent-pending thermal heat sinks. The HP Series is designed for performance in high ambient temperatures up to 50°C.

FEATURES:

- 5 year limited warranty, 10 year warranty available
- Power Factor > 0.9
- 0-10V Dimming
- Beam angle 105°
- Polycarbonate shade with drop lens optional
- Indoor / Damp rated

CONSTRUCTION:

- Innovative ALDC12 die cast heat sinks for exceptional thermal performance even in high ambient temperatures
- White powder coated standard
- 3/4" NPT steel hook standard
- 4 ft whip



Highbay with battery backup and integrated sensor

MODEL SELECTION					Typical order example: HP-130UF-40EMMSC				
HP	-				-				
FAMILY	-	WATTAGE	VOLTAGE	LENS	-	CCT	BBU	CORD SET	OPTIONS
HP= High Bay Pendant	-	090= 90W 130= 130W 160= 160W 185= 185W	U= 120-277V H= 347-480V	(OMIT)= No Lens F= Frosted	-	40= 4000K 50= 5000K	(OMIT)= None EM= Battery Backup	(OMIT)= None C1= 120V cord and plug C2= 277V cord and plug C3= 347V cord and plug C4= 480V cord and plug	(OMIT)= None MSO= On/Off Motion Sensor MSC= Bi-Level w/ Remote Capability MSV= Bi-Level Motion Sensor MSM= Bi-Level Microwave Motion Sensor

* To stem mount product, remove hook in the field.

** Battery backup provides 2800 lumens for 90 minutes

*** Battery backup and optional cords cannot be used together

**** Battery backup cannot be used with 347-480V product

***** When high voltage is required, MSC is the only sensor option available

SPECIFICATIONS:

		HP-090UF-50	HP-130UF-50	HP-160UF-50	HP-185UF-50
ITEM	SPECIFICATION	DETAILS			
GENERAL PERFORMANCE	Power Consumption (W)	88.1	129.7	159.5	180.2
	Equivalent Wattage	175W	250W	400W	600W
	Lumens Delivered (lm)	12,100	17,900	22,260	25,770
	Efficacy (lm/W)	137 lm/W	138 lm/W	140 lm/W	143 lm/W
	CRI	≥80			
	Color Temperature (K)	5000K (4000K available, contact MaxLite for info.)			
	L70 Lumen maintenance (hours)	100,000			
	Color Consistency	Proprietary binning for uniform color			
ELECTRICAL	Power Factor	>0.9			
	Input Voltage	120-277V (347-480V optional)			
	Dimming	0-10V, to 10%			
PHYSICAL	Mounting	Hook Standard, optional 3/4" pipe, wall			
	Operating Temperature	-40°F to 122°F (-40°C to 50°C)			
	Humidity	10-90% RH, non-condensing			
QUALIFICATION	Qualification	DLC Premium, UL, FCC, LM79			
	Material Usage	RoHS compliant; no mercury			
	Environment	Indoor / Damp			
	Warranty	5 Years			

*To stem mount product, remove hook in the field.

ORDERING*:

ORDER CODE	MODEL NUMBER	INVENTORY	WATTAGE	MOUNTING	CCT
1410223	HP-090UF-50	Stocked	90	Hook	5000K
1410225	HP-130UF-50		130		
1410227	HP-160UF-50		160		
1410229	HP-185UF-50		185		
1410222	HP-090UF-40	Special Order	90		4000K
1410224	HP-130UF-40		130		
1410226	HP-160UF-40		160		
1410228	HP-185UF-40		185		

*Please contact your MaxLite representative to order products that don't have order codes listed here.

OTHER ACCESSORIES:

ORDER CODE	MODEL NUMBER	DESCRIPTION	PRODUCT IMAGE
14099234	HP-SHADEKIT-FR	Polycarbonate Frosted Shade w/ Installation Screws	
100666	HP-DRPLNSKIT	Polycarbonate Drop Lens w/ Installation Clips *Shade is required for use of drop lens	
100250	HP-WMB	Surface Mount Bracket	
14099154	HP-WGW	Wire Guard	
101286	BLHTD120-12/5	10' Modular Wiring Drop (120V)	
75324	BLHTD277/480-12/5	10' Modular Wiring Drop (277/480V)	
103492	RMTITXSRP280	MSC Sensor Remote	
102184	FSIR-100	High Voltage MSC Sensor Remote	

* Wire Guard not compatible with shade or drop lens

SENSOR INFORMATION:

SENSOR OPTION	DESCRIPTION	QR CODE FOR SENSOR INFORMATION
MSO	On/Off Motion Sensor with set point daylight harvesting	
MSV	Bi-Level Motion Sensor with set point daylight harvesting	
MSC	Bi-Level Motion Sensor with daylight harvesting and remote control capability (Remote purchased separately)	QR Code Coming Soon


OPERATIONAL DATA:

	NOMINAL WATTAGE	NO LENS			FROSTED LENS		
		LUMENS	EFFICACY	WATTAGE AT 120V	LUMENS	EFFICACY	WATTAGE AT 120V
Delivered Lumens, 4000K	90W	13,060	147.7	88.4	11,823	133.8	88.4
	130W	19,325	148.3	130.2	17,495	134.4	130.3
	160W	24,073	150.8	159.6	21,794	136.6	159.7
	185W	27,860	154.3	180.6	25,222	139.7	180.5
Delivered Lumens, 5000K	90W	13,384	151.9	88.1	12,100	137.3	88.1
	130W	19,797	152.6	129.7	17,897	138.0	129.7
	160W	24,627	154.4	159.5	22,264	139.6	159.5
	185W	28,501	158.2	180.2	25,766	143.0	180.2


CURRENT TABLE:

NOMINAL WATTAGE	VOLTAGE	
	120V-277V	347-480V
90W	0.74-0.33	0.26-0.2
130W	1.09-0.48	0.39-0.3
160W	1.37-0.59	0.45-0.34
185W	1.54-0.66	0.53-0.39

WATTAGE VS LUMENS:



The products used for this table were measured at 120V and 5000K CCT



LUMEN MAINTENANCE:

Time	10,000	20,000	30,000	40,000	50,000	60,000	70,000	80,000	90,000	100,000
Lumen Maintenance	96.99%	94.58%	92.22%	89.92%	87.68%	85.49%	83.36%	81.28%	79.26%	77.28%