

## Exit & Emergency

### Evade Exit/Emergency Combination Series

- LED Life-Cycle exceeding 10 years
- Red & Green Face
- Dual Voltage 120 or 277 VAC Input
- Remote Capability Option
- Fully Rotatable Heads
- Single & Double Face Configurations

### Specifications

#### Description

The Evade Series Exit and Emergency Combo Family offers a quality exit and emergency lighting solution for hallway, stairwell and other Life Safety applications. The low profile design makes it ideal to mount on walls or ceilings indicating and illuminating the path of egress for a minimum of 90 minutes after a power loss.

#### Electrical

- 120 or 277 VAC Input
- Test Emergency Button and Battery Charging Indicator
- Long-Life Maintenance Free NiCad Battery
- 24 Hour Recharge Time
- Battery Low Voltage Protection Circuit
- .75W Lamp Heads Delivering 150 Total Lumens at CCT of 5700K

#### Certifications

- UL924
- NFPA 101 and NFPA 70
- CEC T20 Compliant
- Damp Location Listed



#### Construction & Mounting

- Injection-Molded Thermoplastic Housing with 5VA Flame Retardant
- Exit Lettering 6" height and 3/4" Stroke
- Snap In and Out Chevrons
- Suitable for Wall and Ceiling Mount
- Universal J-Box Mounting Pattern on Back Plate

# Evade Exit/Emergency Combination Series

## Ordering Information

| Product SKU  | Product Code | Product Description   |
|--------------|--------------|---|
| 95004        | EV-EXC-GR    | Evade Exit Sign & Emergency Combination Unit with Green Lettering                       |
| 95005        | EV-EXC-RD    | Evade Exit Sign & Emergency Combination Unit with Red Lettering                         |
| 95006        | EV-EXC-GR-RC | Evade Exit Sign & Emergency Combination Unit with Green Lettering and Remote Capability |
| 95007        | EV-EXC-RD-RC | Evade Exit Sign & Emergency Combination Unit with Red Lettering and Remote Capability   |
| Remote Heads |              |   |
| 95010        | EV-RH-1-IND  | Evade Single Remote Indoor Head   |
| 95011        | EV-RH-2-IND  | Evade Dual Remote Indoor Head   |
| 95012        | EV-RH-1-OUT  | Evade Single Remote Outdoor Head  |
| 95013        | EV-RH-2-OUT  | Evade Double Remote Outdoor Head  |

## Specifications Table

|                                  | EV-EXC-GR                                | EV-EXE-RD | EV-EXE-GR-RC          | EV-EXE-RD-RC |
|----------------------------------|--|-----------|-----------------------|--------------|
| <b>Letter Color</b>              | Green                                    | Red       | 80mA Max              | 100mA Max    |
| <b>Input</b>                     | 30mA Max                                 |           | 33mA Max              |              |
| <b>Wattage</b>                   | 2.8W                                     |           | 3.5W                  |              |
| <b>Battery</b>                   | Ni-cad 3.6V900mAh                        |           | Ni-cad 3.6V900mAh (2) |              |
| <b>Lamp Head Wattage</b>         | .75W Ea (1.5W Total)                     |           |                       |              |
| <b>Lamp Head Lumens</b>          | 150 LM                                   |           |                       |              |
| <b>Recharge Time</b>             | 24 Hours                                 |           |                       |              |
| <b>Voltage</b>                   | 120 or 277 VAC                           |           |                       |              |
| <b>Frequency</b>                 | 60Hz                                     |           |                       |              |
| <b>Housing</b>                   | Injection-Molded Thermoplastic Housing   |           |                       |              |
| <b>Testing Function</b>          | Manual Push to Test Button               |           |                       |              |
| <b>Operating Temperature</b>     | 10°C to 40°C                             |           |                       |              |
| <b>Listings &amp; Compliance</b> | UL 924, CEC Title 20, NFPA 70 & NFPA 101 |           |                       |              |
| <b>Environment</b>               | Damp Location Listed                     |           |                       |              |
| <b>Warranty</b>                  | 2 Year Battery                           |           |                       |              |

## Evade Exit/Emergency Combination Series

### Remote Head Specifications

| Product SKU | Product Code | Input Voltage | Input Wattage | Lumens |
|-------------|--------------|---------------|---------------|--------|
| 95010       | EV-RH-1-IND  | 3.6VDC        | .75W          | 85     |
| 95011       | EV-RH-2-IND  | 3.6VDC        | 1.5W          | 170    |
| 95012       | EV-RH-1-OUT  | 3-12VDC       | .75W          | 90     |
| 95013       | EV-RH-2-OUT  | 3-12VDC       | 1.5W          | 180    |

### Remote Head

#### EV-RH-IND

- Single Remote Indoor Head
- Suitable for Damp Location. UL, cUL Listed



#### EV-RH-2 IND

- Dual Remote Indoor Head
- Suitable for Damp Location. UL, cUL Listed



#### EV-RH-1-OUT

- Single Remote Outdoor Head
- Suitable for Wet Location. UL, cUL Listed



#### EV-RH-2-OUT

- Dual Remote Outdoor Heads
- Suitable for Wet Location. UL, cUL Listed



### Dimensions

