

Exit & Emergency

Evade Exit Series

- LED Life-Cycle exceeding 10 years
- Red & Green Face
- Dual Voltage 120 or 277 VAC Input
- Remote Capability Option
- Multiple Mounting Options
- Single & Double Face Configurations

Specifications

Description


The Evade Series Exit Family offers a quality exit lighting solution for hallway, stairwell and other Life Safety applications. The low profile design makes it ideal to mount on walls or ceilings indicating the path of egress for a minimum of 90 minutes after a power loss.

Electrical

- 120 or 277 VAC Input
- Test Emergency Button and Battery Charging Indicator
- Long-Life Maintenance Free NiCad Battery
- 24 Hour Recharge Time

Certifications

- UL924
- NFPA 101 and NFPA 70
- CEC T20 Compliant
- Damp Location Listed



Construction & Mounting

- Injection-Molded Thermoplastic Housing with 5VA Flame Retardant
- Exit Lettering 6" height and 3/4" Stroke
- Snap In and Out Chevrons
- Suitable for Wall, Ceiling and End Mount
- Universal J-Box Mounting Pattern on Back Plate

Evade Exit Series

Ordering Information

Product SKU	Product Code	Product Description
95000	EV-EXE-GR	Evade Exit Sign with Green Lettering
95001	EV-EXE-RD	Evade Exit Sign with Red Lettering
95002	EV-EXE-GR-RC	Evade Exit Sign with Green Lettering and Remote Capability
95003	EV-EXE-RD-RC	Evade Exit Sign with Red Lettering and Remote Capability
Remote Heads		
95015	EV-RHE-1-IND	Evade Exit Single Remote Indoor Head
95016	EV-RHE-2-IND	Evade Exit Double Remote Indoor Head
95012	EV-RH-1-OUT	Evade Single Remote Outdoor Head
95013	EV-RH-2-OUT	Evade Double Remote Outdoor Head

Specifications Table

	EV-EXE-GR	EV-EXE-RD	EV-EXE-GR-RC	EV-EXE-RD-RC
Letter Color	Green	Red	Green	Red
Input	.30mA Max		.40mA Max	
Wattage	2.3W		2.7W	
Battery	Ni-cad 2.4V300mAh		N-cad HT 4.8V1000mAh	
Recharge Time	24 Hours			
Voltage	120 or 277 VAC			
Frequency	60Hz			
Housing	Injection-Molded Thermoplastic Housing			
Testing Function	Manual Push to Test Button			
Operating Temperature	10°C to 40°C			
Listings & Compliance	UL 924, CEC Title 20, NFPA 70 & NFPA 101			
Environment	Damp Location Listed			
Warranty	2 Year Battery			

Exit & Emergency

Evade Exit Series

Remote Head Specifications

Product SKU	Product Code	Input Voltage	Input Wattage	Lumens
95015	EV-RHE-1-IND	4.8VDC	.8W	53
95016	EV-RHE-2-IND	4.8VDC	1.44W	96
95012	EV-RH-1-OUT	3-12VDC	.75W	90
95013	EV-RH-2-OUT	3-12VDC	1.5W	180

Remote Head

EV-RHE-1-IND

- Single Remote Indoor Head
- Suitable for Damp Location. UL, cUL Listed



EV-RHE-2-IND

- Double Remote Indoor Head
- Suitable for Damp Location. UL, cUL Listed



EV-RH-1-OUT

- Single Remote Outdoor Head
- Suitable for Wet Location. UL, cUL Listed



EV-RH-2-OUT

- Dual Remote Outdoor Heads
- Suitable for Wet Location. UL, cUL Listed



Dimensions

