



# KT-MSLED18-4-8XX-VDIM-P

## LED MICROSTRIP FIXTURE

### DESCRIPTION

4' 18W LED Microstrip Fixture | 120–277V Input | Frosted Lens | 0–10V Dimming | Premium Series

### APPLICATION

Used for commercial, retail, and residential strip applications



### PRODUCT FEATURES


- Powered by Keystone 0–10V dimming LED drivers
- Smooth diffused lens for an even appearance
- 0–10V dimming, 10% minimum
- Compatible with Keystone SmartSafe emergency LED drivers; KT-EMRG-LED-5-500 /NB or KT-EMRG-LED-12-1200 /NB are optimal for fixture level installation
- Compatible with Keystone 480–277V step down transformers
- Compatible with Keystone occupancy sensors
- Ambient operating temperature: –20°C/–4°F to 50°C/122°F
- UL Listed 1598: Suitable for dry and damp locations
- THD: <20%
- Power factor >0.95
- L70 >50,000 hours
- DLC Premium Listed

### PRODUCT SPECIFICATIONS

Catalog Number	Color Temperature	Nominal Length	Input Voltage	Wattage	CRI	Lumen Output	Efficacy
KT-MSLED18-4-835-VDIM-P	3500K	4 ft.	120–277V	18W	>82.0	2,290	127 lm/W
KT-MSLED18-4-840-VDIM-P	4000K	4 ft.	120–277V	18W	>82.0	2,320	129 lm/W
KT-MSLED18-4-850-VDIM-P	5000K	4 ft.	120–277V	18W	>82.0	2,340	130 lm/W

### PHOTOMETRIC SPECIFICATIONS

#### ISOCANDELA PLOT



- Cd: 578, 90%
  - Cd: 481, 75%
  - Cd: 385, 60%
  - Cd: 321, 50%
  - Cd: 257, 40%
  - Cd: 193, 30%
  - Cd: 128, 20%
  - Cd: 64, 10%
- Point of Max Cd: 642.9

#### ZONAL LUMEN SUMMARY


Zone	Lumens	% Luminaire
0–30	496.4	21.9%
0–40	814.4	35.9%
0–60	1,464.6	64.6%
60–90	603.1	26.6%
70–100	422.8	18.6%
90–120	166.2	7.3%
0–90	2,067.6	91.1%
90–180	200.9	8.9%
0–180	2,268.6	100%



# KT-MSLED18-4-8XX-VDIM-P

## LED MICROSTRIP FIXTURE

### PHYSICAL SPECIFICATIONS



### ORDERING INFORMATION

Order Code	Packaging Style	Pack Quantity	Item Status
KT-MSLED18-4-835-VDIM-P	Carton Pack	1	Active
KT-MSLED18-4-840-VDIM-P	Carton Pack	1	Active
KT-MSLED18-4-850-VDIM-P	Carton Pack	1	Active

### ACCESSORIES (SOLD SEPARATELY)

Accessory	Catalog Number	Description
SmartSafe Emergency Battery Backup	KT-EMRG-LED-5-500 /NB	5W, 500 lumen SmartSafe emergency battery backup with narrow battery
	KT-EMRG-LED-12-1200 /NB	12W, 1200 lumen SmartSafe emergency battery backup with narrow battery
V-Hooks for Suspended Mounting	KT-MSLED-VH-KIT	Two (2) V-Hooks and chains for chain-suspended mounting

### CATALOG NUMBER BREAKDOWN

# KT-MSLED18-4-8XX-VDIM-P

1 2 3 4 5 6 7 8

- 1 Keystone Technologies
- 2 LED Microstrip Fixture
- 3 Wattage
- 4 4' Nominal Length
- 5 800 Series
- 6 Color Temperature
- 7 0-10V Dimming
- 8 Premium Series