



CUBE : LED WALLPACK

FEATURES

- Economical and energy efficient LED solution for general purpose wall mount lighting
- Includes integrated photocell

LISTINGS

- UL Listed for wet locations
- IP65 Rated
- DesignLights Consortium® Premium Qualified - meets the requirements for the highest DLC qualification for efficacy and lumen maintenance

LED CHARACTERISTICS

- Rated lifetime L70: 50,000 hours
- FieldCCeT: 3000K/4000K/5000K selectable
- CRI: >70

ELECTRICAL

- Input voltage: 120-277V
- 0-10V dimming
- Power Factor: >.90
- THD: <20%

CONSTRUCTION

- Durable die cast aluminum housing with polycarbonate impact-resistant lens
- -4°F to 113°F (-20°C to 45°C) operating temperature

WARRANTY

- 5 year limited warranty. Additional warranty options available. Contact EiKO for details

project name	type
catalog number	
comments	voltage
approved by	date



APPLICATIONS

- Residential Exteriors
- Entrances
- Storage Facilities
- Convenience Stores
- Recreational Areas
- Housing Complexes
- Security



ORDERING INFORMATION

EXAMPLE: WPC-195-15W-7CCT3-UD-PC-BZ

Model	Lumens	Watts	CRI/CCT	Voltage	Dimming	Photocell	Finish
WPC : LED Wallpack Cube	195 - 1,950 lm	15W - 15W	7CCT3 - >70 CRI; 30/40/5000K	U - 120-277V	D - 0-10V Dimming	PC - Photocell	BZ - Bronze
	260 - 2,600 lm	20W - 20W					

PERFORMANCE SUMMARY

Order Code	Item #	Watts	Lumens	CCT	CRI	Volts	DLC Premium
11158	WPC-195-15W-7CCT3-UD-PC-BZ	15W	1,950	30/40/5000K	70+	120-277V	✓
11159	WPC-260-20W-7CCT3-UD-PC-BZ	20W	2,600	30/40/5000K	70+	120-277V	✓

✓DesignLights Consortium® Qualified

DIMENSIONS

