

LED T8 - LINEAR REPLACEMENT LAMP
DIRECTFIT COATED GLASS SERIES 5
UL TYPE-A



Intertek



PRODUCT DESCRIPTION:

MaxLite DirectFit LED T8 lamp is the ideal plug and play solution that works straight out of the box. Designed to deliver between 1800- 1900 lumens, these energy-saving LED lamps are quick, easy and safe to install into existing linear fluorescent fixtures without any extra effort or re-wiring. MaxLite DirectFit LED T8 lamps utilize the existing T8 instant-start electronic ballasts, thus minimizing maintenance and labor costs. Tested to NSF Standards, these lamps carry the **ETL Sanitation Mark** and are suitable for use in an environment where food intended for human consumption is produced.

FEATURES:

- Wattage: 13W
- Lumens: 1800-1900
- Input Voltage: 120-347 VAC, determined by fluorescent ballast
- Compatible with most electronic instant-start and programmed rapid start T8 ballasts, emergency ballast, and dimming ballasts
- 330° beam angle
- Color Rendering Index (CRI): 83
- 50,000 hour life (L70 standards)
- THD: <20%
- UV Free
- Power Factor: 0.90 nominal
- Dimmable (ballast dependent)
- Five year limited warranty
- Suitable for use in dry locations
- Suitable for damp locations
- Suitable for use in totally enclosed recessed fixture
- Not for use with T12 magnetic or electronic ballasts
- Not for use with T8 magnetic or HO ballasts
- Not for use or to be wired to "mains voltage"

4FT MODEL SELECTION (Full list of order codes on pg. 3)

Typical order example: L13T8DF450-CG5

L13	T8	DF	4	
FAMILY	LAMP TYPE	OPERATION	LENGTH	CCT
L13= LED Linear, 13W	T8= T8 tube	DF= Direct Fit	4= 4 FT	35-CG5= 3500K, Coated Glass 40-CG5= 4000K, Coated Glass 50-CG5= 5000K, Coated Glass

SPECIFICATIONS:

		L13T8DF4xx-CG5		
ITEM	SPECIFICATION	4FT - DETAILS		
GENERAL PERFORMANCE	Bare Lamp Wattage (W)	13W		
	Lumens Delivered* (lm)	1800	1850	1900
	Color Temperature (CCT)	3500K	4000K	5000K
	Efficacy (lm/W)	112	115	118
	CRI	83		
	Beam Angle	330°		
	Lumen Maintenance (L70)	50,000 hours		
ELECTRICAL	Power Factor	≥ 0.90		
	Input Voltage	120-347V, ballast dependent		
PHYSICAL	Operating Temperature	-4°F to 113°F		
CERTIFICATION	Certification	UL Listed, ETL Sanitation Listed, DLC 4.2 Standard		
	Material Usage	RoHS compliant, no mercury		
	Environment	Dry, Damp		
	Warranty	5 Years		

* Operating with normal ballast factor (.88) ballast

WATTS & LUMENS*:

				AVERAGE SYSTEM WATTS				INITIAL LUMENS		
ORDER CODE	MODEL	CCT	CASE QTY	BARE LAMP WATTAGE	LOW BF= .78	NORMAL BF= .88	HIGH BF= 1.18	LOW BF= .78	NORMAL BF= .88	HIGH BF= 1.18
4FT T8										
14098818	L13T8DF435-CG5	3500K	25	13	14	16	22	1600	1800	2600
14098819	L13T8DF440-CG5	4000K		13	14	16	22	1650	1850	2650
14098820	L13T8DF450-CG5	5000K		13	14	16	22	1700	1900	2750

* Lumens and watts will vary by ballast and fixture

COMPATIBLE BALLASTS - INSTANT START 120-277V:

MANUFACTURER	MODEL	BALLAST VERSION	BALLAST FACTOR	# OF LAMPS	COMPATIBILITY
ARCATA	ACT2P32ISUNV	-	Normal	2	GOOD
	ACT4P32ISUNV	-	Normal	4	GOOD
ACCUPRO	AP-RC-232IP-120-1	-	Normal	2	GOOD
	A3-RC-232IP-120-1	-	Normal	2	GOOD
DAMAR	1688A	-	Normal	2	GOOD
EIKO	PM 2x32T8-UNV-IS-L	-	Normal	2	GOOD
ESPEN	VE232MVHIP	-	Normal	2	GOOD
	VE232MVHIPE	-	Normal	2	GOOD
	VE232MVHIPHE	-	High	2	GOOD
	VE232MVHIPLE	-	Low	2	GOOD
	VE432MVHIP	-	Normal	4	GOOD
	VE432MVHIPE	-	Normal	4	GOOD
	VE432MVHIPHE	-	High	4	GOOD
FULHAM	NPY-120-432-T8B	-	N/A	4	GOOD
	NPY-120-432-T8-IS	-	N/A	4	GOOD
	WHCG3-120-T8-IS	-	Normal	3	GOOD
	WH2-120-L	-	Normal	1	GOOD
	WH5-120-L	-	Normal	4	GOOD
FUSION	FB232MVE	-	N/A	2	GOOD
	FB232MVE-HE	-	N/A	2	GOOD
	FB232MVE-LHE	-	N/A	2	GOOD
	FB332MVE	-	N/A	3	GOOD
	FB432MVE	-	N/A	4	GOOD
	FB432MVE-HE	-	N/A	4	GOOD
GE	GE132MAXP-N/ULTRA	-	Normal	1	GOOD
	GE 232-120RES-DIYB	-	Normal	2	GOOD
	GE232MAX-G-N	-	Normal	2	GOOD
	GE232MAXP-L/ULTRA	-	Low	2	GOOD
	GE232MAXP-N/ULTRA	-	Normal	2	GOOD
	GE232MAXP-H/ULTRA	-	High	2	GOOD
	GE232-MV-N	-	Normal	2	GOOD
	GE332MAX-L/ULTRA	-	Low	3	GOOD
	GE332MV-N-DIY	-	Normal	3	GOOD
	GE432MAX-G-N	-	Normal	4	GOOD
	GE432MAX-H/ULTRA	-	High	4	GOOD
	GE432MAX-H-42T	-	High	4	GOOD

Please contact MaxLite for questions about third party ballasts that are not on this list.

COMPATIBLE BALLASTS - INSTANT START 120-277V (CONTINUED):

MANUFACTURER	MODEL	BALLAST VERSION	BALLAST FACTOR	# OF LAMPS	COMPATIBILITY
GREENHILL	GH2P59ISUNV	-	N/A	2	GOOD
	GH4P32ISUNV	-	N/A	4	GOOD
HALCO	EP232IS/H/MV/HE	-	High	2	GOOD
	EP332IS/L/MV/HE	-	Low	3	GOOD
	EP332IS/MV/MC	-	High	3	GOOD
	EP432IS/L/MV/HE	-	Low	4	GOOD
	EP432IS/MV/MC	-	N/A	4	GOOD
HOWARD	EP3/32IS/MV/SC/HE	-	Low	3	GOOD
	EP4/32IS/MV/MC/HE	-	Normal	4	GOOD
HUAFENG	ENI-T8-32-P2SC-N	-	N/A	2	GOOD
	ENI-T8-32-P4MC-N	-	N/A	4	GOOD
KEYSTONE	KTEB-232-UV-IS-N-P	Version D1	Normal	2	GOOD
	KTEB-332-UV-IS-N-P	Version B	High	3	GOOD
	KTEB-432-UV-IS-N-P	Version A1	Normal	4	GOOD
MAXLITE	MLEU322HE/SC	-	Normal	2	GOOD
OSRAM	QHE 2x32T8/UNV ISL SC	-	Low	2	GOOD
	QTP 2x32T8/UNV ISN-SC	-	Normal	2	GOOD
	QTP 4x32T8/UNV ISN-SC	-	Normal	4	GOOD
PACIFIC	EB-332IS-U	-	Normal	3	GOOD
	EB-432IS-U	-	Normal	4	GOOD
PHILIPS ADVANCE	ICN-1P32-N	-	Normal	1	GOOD
	ICN-2P32-N	Version C/E	Normal	2	GOOD
	ICN-2P32-SC	-	Normal	2	GOOD
	ICN-3P32-N	Version D	Normal	3	GOOD
	GOPA-2P32-SC	-	Normal	2	GOOD
	ICN-2M32-MC	-	Normal	2	GOOD
	ICN-2P32-N	-	Normal	2	GOOD
	IOPA-1P32-N	Version B	Normal	1	GOOD
	IOPA-2P32-N	Version A	Normal	2	GOOD
	IOPA-4P32-N	Version C	Normal	4	GOOD
	IOPA-1P32-LW-N	Version A	Low	1	GOOD
	IOPA-2P32-LW-N	Version B	Low	2	GOOD
	IOPA-4P32-LW-N	Version A	Low	4	GOOD
	REB-2P32-SC	-	Normal	2	GOOD
	REL-2P32-SC	-	Normal	2	GOOD
	REL-4P32-RH-TP	-	Normal	4	GOOD
	ICN-4P32-N	Version D	Normal	4	GOOD
	ICN-4P32-SC	Version D	Normal	4	GOOD
	IOP-4P32-LW-N	-	Low	4	GOOD
	VEL-1P32-SC	-	Normal	1	GOOD

Please contact MaxLite for questions about third party ballasts that are not on this list.

Specifications are subject to change without notice.

Phone: 1-800-555-5629 | Fax: 973-244-7333 | Web: www.maxlite.com | E-mail: info@maxlite.com

MAX17155
Revised:12-07-17



COMPATIBLE BALLASTS - INSTANT START 120-277V (CONTINUED):

MANUFACTURER	MODEL	BALLAST VERSION	BALLAST FACTOR	# OF LAMPS	COMPATIBILITY
PLUSRITE	BAF232IS/MV/H	-	N/A	2	GOOD
PREMIUM	BB-T8/UVH-2x32	-	Normal	2	GOOD
	BB-T8/UVH-3x32	-	N/A	3	GOOD
PQL	70201	-	N/A	2	GOOD
	70204	-	N/A	4	GOOD
STANDARD	E232PI120L	-	Normal	2	GOOD
	E232T8IS120/L/AS	-	Low	2	GOOD
	E232T8IS120/N/AS	-	Normal	2	GOOD
	E432T8IS120/H	-	High	4	GOOD
	E432T8IS120/L/AS/BULK	-	Low	4	GOOD
	E432T8IS120/N/AS/BULK	-	Normal	4	GOOD
UNIVERSAL TRIAD	B232IUNVHP-N	Version B	Normal	2	GOOD
	B332IUNVHP-A	Version B	Normal	3	GOOD
	B432IUNVHP-A	Version B	Normal	4	GOOD

Please contact MaxLite for questions about third party ballasts that are not on this list.

COMPATIBLE BALLASTS - INSTANT START 347-480V:

MANUFACTURER	MODEL	BALLAST VERSION	BALLAST FACTOR	# OF LAMPS	COMPATIBILITY
ARCATA	ACT2P32IS347	-	Normal	2	GOOD
	ACT4P32IS347	-	Normal	4	GOOD
ADVANCE	GOPA-2P32-LW-SC	Version D	Low	2	GOOD
	GOPA-4P32-LW-SC	Version D	Low	4	GOOD
	GOPA-2P32-SC	Version C	Normal	2	GOOD
	GOPA-4P32-SC	Version C	Normal	4	GOOD
Fusion	FB232347E-HE	-	N/A	2	GOOD
	FB232347E-L	-	N/A	2	GOOD
	FB432347E-HE	-	N/A	4	GOOD
	FB432347E-L	-	N/A	4	GOOD
GE	GE232MAX347-H	-	High	2	GOOD
	GE332MAX347-H	-	High	3	GOOD
	GE432MAX347-H	-	High	4	GOOD
OSRAM	QHE 2x32 T8/347 ISL-SC	-	Low	2	GOOD
	QHE 2x32 T8/347 ISN-SC	-	Normal	2	GOOD
STANDARD	E232T8IS347/H/90C	-	N/A	2	GOOD
	E232T8IS347/L/BULK	-	N/A	2	GOOD
	E232T8IS347/N/BULK	-	N/A	2	GOOD
	E432PI347G01	-	N/A	4	GOOD
	E432T8IS347/L/BULK	-	N/A	4	GOOD
	E432T8IS347/N	-	N/A	4	GOOD
	E432T8IS347/N/BULK	-	N/A	4	GOOD
	E432T8IS347/H/90C	-	N/A	4	GOOD
ULTRASAVE	MR232347	-	N/A	2	GOOD
UNIVERSAL	B232I347HE-A	-	Normal	2	GOOD
	B432I347HE-A	-	N/A	4	GOOD

Please contact MaxLite for questions about third party ballasts that are not on this list.

COMPATIBLE BALLASTS - PROGRAM/RAPID START 120-277V:

MANUFACTURER	MODEL	BALLAST VERSION	BALLAST FACTOR	# OF LAMPS	COMPATIBILITY
FULHAM	NPY-120-232-LT8	-	Normal	2	GOOD
	WHCG5-120-T12-RS	-	Normal	2	GOOD
FUSION	FB232MVE-PPS-HE	-	N/A	2	GOOD
	FB432MVE-PPS-HE	-	N/A	4	GOOD
GE	GE232-MVPS-L	-	Low	2	GOOD
	GE232-MVPS-N	-	Normal	2	GOOD
	GE232-MVPS-H	-	High	2	GOOD
OSRAM	QTP 3x32T8/UNV PSX-SC	-	Low	3	GOOD
	QHE 4x32T8/UNV PSN-SC	-	Normal	4	GOOD
ROBERTSON	RSW240T12120	-	N/A	2	GOOD
SUNPARK	SL15T	-	Normal	2	GOOD
TCP	E4P32PSUNVE	-	Normal	4	GOOD
PHILIPS ADVANCE	ICN-2S40-N	-	Normal	2	GOOD
	RCN-2S32-SC	Version D	Normal	2	GOOD
	RELB-2S40-N	-	Normal	2	GOOD

Please contact MaxLite for questions about third party ballasts that are not on this list.

COMPATIBLE BALLASTS - PROGRAM/RAPID START 347-480V:

MANUFACTURER	MODEL	BALLAST VERSION	BALLAST FACTOR	# OF LAMPS	COMPATIBILITY
FUSION	FB232347E-PPS-HE	-	N/A	2	GOOD
	FB432347E-PPS-HE	-	N/A	4	GOOD

COMPATIBLE EMERGENCY BALLASTS:

MANUFACTURER	MODEL
IOTA	ISL-540
	ISL-54
	I-320
	ELI-S-20

MANUFACTURER	MODEL
KEYSTONE	KT-EMRG-500
	KT-EMRG-1400-SL
	KT-EMRG-1300-T5

MANUFACTURER	MODEL
PHILIPS BODINE	B50
	ELI-S-20
	LP600
	B50ST

DIMMABLE BALLASTS:

MANUFACTURER	MODEL	BALLAST VERSION	BALLAST FACTOR	# OF LAMPS	COMPATIBILITY
PHILIPS ADVANCE	REZ-2S32-SC	Version E	Normal	2	GOOD
GE	GE332MAX90-V60	-	High	3	GOOD
KEYSTONE	KTEB-232-UV-PS-VDIM	-	High	2	GOOD
OSRAM	QHE 2x32T8/UNV DIM-TC	-	Normal	2	GOOD
UNIVERSAL TRIAD	B232PUSV3PLA	Version A	N/A	2	GOOD
	B232SR120S30	Version E	N/A	2	GOOD