LED-8084M 45W LED for HID Retrofit for Post Top / Wall Pack



Models

LED-8084MXX, 120-277VAC, cULus, 3000K, 4200K or 5700K CCT, E39

Features


- > 45W LED Replaces 175W MH or HPS HID Lamps
- > Meanwell PWM & 0-10V Dimmable driver
- > Driver can be mounted up to 20 meters from lamps with negligible reduction in light output.
- > UL approved for wet environments
- > 50,000 hour rated LED life (supported by LM80 and ISTMT reports (see website)
- > 5 Year Limited Warranty see website for details
- > UL1598C retains fixture UL Listing
- > Rated for enclosed fixture

	1,000			
Technical S	pecifica	tions		
Models US/CAN	LED-8084M30	LED-8084M42	LED-8084M57	
ССТ	3000K	4200K	5700K	
Power Consumption		45 watts		
Replaces	1	75 MH/HF	PS	
Mounting		E39		
Voltage	120-277VAC (USA)			
LED Type	Samsung #5630 SMD			
Beam Angle	360°			
Dimmable	Yes			
Operating Temp	-40	-40°F - +122°F		
Rated R70 Life	Up to 50,000 Hrs.			
Warranty	5 Year Limited*			
LM79 Specifications	Yes	Yes	Yes	
Power (W)	43.5	44.1	43.8	
ССТ	3136	4085	5782	
Light Output	4062	4273	4509	
Efficacy	93.4	96.9	102.7	
THD @ 277V	12.70%	12.70%	12.60%	
PF @ 277V	0.918	0.921	0.919	
CRI:	84.4	84.4	85.8	
R9	18	27	11	
Duv	-0.0005	-0.0005	0.0024	
Packaging	4 / Master Carton			
Unit	7.5" x 5.44" x 12" 3.99 lbs.			
Master	15.8" x 11.6" x 12.6" 25.5 lbs.			




- 0-10V / PWM DIMMING

1.5"





Polar Curves



ALC DY.	MODEL	DLC CODE
	LED-8084M57	PCCGYSKP
Visita	LED-8084M42	PZPJGUXQ

Approved Categories: Replacement Lamps for Outdoor Pole/Arm-m

Installation Notes:

- Ballast must be bypassed
- · Installing surge/lightning protectors is highly recommended

	LED Power Consumption (Watts)	HID Power Consumption (Watts)	HID Ballast Power Consumption (Watts)	Total Savings (Watts)	Annual Energy Savings (14 hrs/day)	Lifetime Energy Savings (over 50,000 hrs)
L	45	175	35	165	\$93	\$907.50

Mounting Orientation		Minimum Fixture Size		
Base Up	Base Down	Horiz	Requirements (inches)	
			Length	12.52
			Width	5.93
# #			Height	5.93
			Cu. Inches	440.3
Approved	Approved	Approved	Cu. Iliches	



