LEDone®


PRODUCT DESCRIPTION:

Energy-saving lamps and lanterns, high lumen, perfect color temperature and high CRI characteristics for offices, schools, retails, medical hospitality and many other interior applications.

FEATURES:

- Default Wattage: 39W
- Multi Wattage Options: 24W, 29W, 32W and 39W
- Default CCT: 5,000K
- Multi CCT Options: 3,500K, 4,000K and 5,000K
- Matte white paint finish
- Glare-free lighting
- The entire fixture functions as a heat sink to keep the LEDs cooler to prolong the life of the light

OPTIONAL ACCESSORIES:





Surface mount kit

Dry wall kit





Aircraft cable

EM



Sensor

Page: 1 of 2

2X4 MULTI WATT MULTI CCT LED TROFFER

LOC-24TROF-DMWMCCT







LEDone Phone: (844) LEDONE6 | Fax: 1-510-217-9461 | Web: www.ledonecorp.com

LEDone®

2X4 MULTI WATT MULTI CCT LED TROFFER

SPECIFICATIONS:

SPECIFICATION	Details			
Model	LOC-24TROF-DMWMCCT			
Input Wattage (W)	24W	29W	32W	39W
Lumens Delivered (LM)	3,060LM	4,060LM	4,480LM	5,460LM
Efficacy (LM/W)	140LM/W			
CRI	80			
Lifespan	100,000 hours			
Color Temperature	3,500К	4,	000K	5,000K
Wattage Equivalent	200W			
Dimmable	0-10V			
Input Voltage	AC120-277V			
Power Factor	0.9			
THD	20%			
Housing				
Lens	Frosted			
Mounting	Surface mount or Dry wall kit or aircraft cable			
Dimension				
Certification				
Operating Temperature	-20-50 °C			
Environment	Inside			
Warranty	5 years			

3000K option is special-order request

•