

LEDone®

Date:	Location:
Product:	Project:
Quantity:	Catalog #:





20W / 30W / 40W / 50W



50W / 60W / 80W / 100W

WATTAGE	BUG RATING				
50W	B3-U1-G1				
100W	B3-U1-G1				

LED Multi Watt Multi CCT Adjustable Wall Pack Light Family Series

CONSTRUCTION:

Heavy die-cast aluminum housing with polyester powder-coated finish. Integral secondary heat sink to optimize thermal transfer and maximize performance of the LEDs.

OPTICAL SYSTEM:

Philips Lumiled 3030 LED chips. High quality tempered glass optics. 100° beam angle.

WARRANTY:

5-year limited warranty. Actual performance may differ as a result of end-user environment and application.

ELECTRICAL:

Available as 120-277V input. -40°C to 40° C, -40°F to 104° F

INSTALLATION & MOUNTING:

Wall mount.

CONTROLS & DIMMING:

0-10V dimming comes standard.

FEATURES

- Default Wattage:
 - o 50W
 - o 100W
- Default CCT: 5,000K
- Photocell included
- IP65 rated
- Easy installation and maintenance
- Corrosion and rust proof
- 50,000 hours lifetime

SUITABLE APPLICATIONS

- Residential Complexes
- Parking Decks
- Shopping Malls
- Sporting Complexes
- Logistic Centers
- Auto dealerships
- Municipal Lots

DLC Product ID:

- LOC-AWP-MW(20/30/40/50)MCCT(30/40/50)D S-YEV8RK
- LOC-AWP-MW(50/60/80/100)MCCT(30/40/50)D S-G9FOKC











LED Multi Watt Multi CCT Adjustable Wall Pack Light Family Series




	LOC-AWP-MW(20/30/40/50)MCCT(30/40/50)D									
WATTAGE SELECTABLE	CCT SELECTABLE	LUMENS	EFFICACY	VOLTAGE	CRI	POWER FACTOR	THD	REPLACES		
20W	3000K / 4000K / 5000K	2,400LM	120lm/W	120-277V	70	0.9	20%	100W		
30W	3000K / 4000K / 5000K	3,600LM	120lm/W	120-277V	70	0.9	20%	100W		
40W	3000K / 4000K / 5000K	4,800LM	120lm/W	120-277V	70	0.9	20%	100W		
50W	3000K / 4000K / 5000K	6,000LM	120lm/W	120-277V	70	0.9	20%	100W		
	LOC-AWP-MW(50/60/80/100)MCCT(30/40/50)D									
WATTAGE SELECTABLE	CCT SELECTABLE	LUMENS	EFFICACY	VOLTAGE	CRI	POWER FACTOR	THD	REPLACES		
50W	3000K / 4000K / 5000K	6,500LM	130lm/W	120-277V	70	0.9	20%	100W		
60W	3000K / 4000K / 5000K	7,800LM	130lm/W	120-277V	70	0.9	20%	150W		
80W	3000K / 4000K / 5000K	10,400LM	130lm/W	120-277V	70	0.9	20%	200W		
100W	3000K / 4000K / 5000K	13,000LM	130lm/W	120-277V	70	0.9	20%	200W		


MEASUREMENTS





20W / 30W / 40W / 50W





50W / 60W / 80W / 100W

MODEL	QUANTITY	WEIGHT	UPC CODE
LOC-AWP-MW(20/30/40/50)MCCT(30/40/50)D	1	4.85 lbs	00810050942737
LOC-AWP-MW(50/60/80/100)MCCT(30/40/50)D	1	8.38 lbs	00810050942744

Phone: (844) LEDONE6 | Fax: 1-510-217-9461 | Web: www.ledonecorp.com