

LED LOC-SL Multi Watt Multi CCT Strip Light with Emergency Battery

4 Foot



8 Foot



FEATURES

- Default Wattage is the highest wattage:
 - 4 Foot – 44W
 - 8 Foot – 90W
- Default CCT: 5,000K
- IP20 rated
- Linkable design (see page 2 for details)
- 50,000 hours lifetime

SUITABLE APPLICATIONS

- Warehouses
- Stadiums
- Factories
- Parking Lots
- Shopping Malls
- Supermarkets
- Logistic Centers
- Auto dealerships

CONSTRUCTION:

22-gauge metal housing with matte white paint. PMMA cover lens. Frosted lens. PC endcaps, quick-connector adaptor for continuous-run mounting.

OPTICAL SYSTEM:

Seoul 2835 LED chips. High quality tempered glass optics. 120° beam angle.

WARRANTY:

5-year limited warranty. Actual performance may differ as a result of end-user environment and application.

ELECTRICAL:

Available as 120-277V input. -20°C to 50°C, -4°F to 122°F

INSTALLATION & MOUNTING:

Hanging chain, surface mount or J-adaptor. These can link together. See above features for how many.

CONTROLS & DIMMING:


0-10V dimming comes standard.



MODEL NUMBER – 3,500K 4,000K 5,000K	WATTAGE	LUMENS	EFFICACY	CRI	POWER FACTOR	THD	REPLACES
LOC-4FTSL-MW(22/28/36/44)MCCT(35/40/50)DF-EM	22W	2,862.2LM	130.1LM/W	80	0.9	20%	2 pieces 17W T8 lamp or 2 pieces 32W T8 lamp
LOC-4FTSL-MW(22/28/36/44)MCCT(35/40/50)DF-EM	28W	3,642.8LM	130.1LM/W	80	0.9	20%	2 pieces 17W T8 lamp or 2 pieces 32W T8 lamp
LOC-4FTSL-MW(22/28/36/44)MCCT(35/40/50)DF-EM	36W	4,683.6LM	130.1LM/W	80	0.9	20%	2 pieces 17W T8 lamp or 2 pieces 32W T8 lamp
LOC-4FTSL-MW(22/28/36/44)MCCT(35/40/50)DF-EM	44W	5,726.9LM	129.77LM/W	84	0.9739	6.82%	2 pieces 17W T8 lamp or 2 pieces 32W T8 lamp
LOC-8FTSL-MW(48/68/90)MCCT(35/40/50)DF-EM	48W	6,590.4LM	137.3LM/W	80	0.9	20%	2 pieces 32W T8 lamp or 4 pieces 32W T8 lamp or 2 pieces 59W T8 lamp
LOC-8FTSL-MW(48/68/90)MCCT(35/40/50)DF-EM	68W	9,336.4LM	137.3LM/W	80	0.9	20%	2 pieces 32W T8 lamp or 4 pieces 32W T8 lamp or 2 pieces 59W T8 lamp
LOC-8FTSL-MW(48/68/90)MCCT(35/40/50)DF-EM	90W	12,062LM	138.98LM/W	84.1	0.9784	13.42%	2 pieces 32W T8 lamp or 4 pieces 32W T8 lamp or 2 pieces 59W T8 lamp

Series	Size	4FT Wattage	8FT Wattage	Color Temperature	Dimming	Material	Accessory
LOC-SL	4FT = 4 foot 8FT = 8 foot	22W 28W 36W 44W	48W 68W 90W	3500K 4000K 5000K	Dimmable	F = Frosted Lens	EM = emergency backup

MEASUREMENTS



MODEL	QUANTITY	WEIGHT	UPC CODE
LOC-4FTSL-MW(22/28/36/44)MCCT(35/40/50)DF-EM	1	lbs	00810050941037
LOC-8FTSL-MW(48/68/90)MCCT(35/40/50)DF-EM	1	lbs	


Emergency Battery




Emergency Test Button




4FT 22W






3,500K




4,000K




5,000K




4FT 28W






3,500K



4,000K




5,000K




PHOTOMETRIC DATA


4FT 36W




3,500K




4,000K




5,000K



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.


4FT 44W




3,500K




4,000K




5,000K



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.






Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.


8FT 48W




3,500K






4,000K




5,000K




8FT 68W




3,500K




4,000K




5,000K




8FT 90W






3,500K




4,000K



5,000K



OPTIONAL MOUNTING & ACCESSORIES



V-Hook (included)



Aircraft Cable




J-Box Cover (included)



Sensor



Remote Control
LOC-RC-100



Bracket for linking
together (included)

LINKING TOGETHER

Model Number	Voltage (18AWG)	Linkable Qty	Voltage (16AWG)	Linkable Qty
LOC-4FTSL-MW(22/28/36/44)MCCT(35/40/50)DF-EM	120V	20	120V	30
	240V	40	240V	65
	277V	50	277V	75
LOC-8FTSL-MW(48/68/90)MCCT(35/40/50)DF-EM	120V	10	120V	15
	240V	21	240V	30
	277V	24	277V	35