

PRODUCT DESCRIPTION:

Designed to fit any ceiling surface. Suspended and hanging for other types of ceilings such as art galleries, homes, schools, offices, hotels, restaurants, retail stores and other commercial or industrial applications.

FEATURES:

- Low maintenance
- Environmentally friendly
- No mercury
- Recyclable

DIMENSIONS:

4" Recessed Downlight 9W Spec

LOD-DL4-9W27K

LOD-DL4-9W30K



SPECIFICATIONS:

SPECIFICATION	Details	
Model	LOD-DL4-9W27K	LOD-DL4-9W30K
Input Wattage (W)	9W	
Lumens Delivered (LM)	659.16LM	700LM
Efficacy (LM/W)	72.40LM/W	77.7LM/W
CRI	91.5	85
Lifespan	36,000 hours	
Color Temperature	2,700K	3,000K
Wattage Equivalent	75W	
Dimmable	Yes	
IP Rating	Damp Location	
Beam Angle	87	
Input Voltage	AC120	
Power Factor	0.87	0.97
Housing	Aluminum	
Lens	Frosted	
Mounting	GU24 or E26	
Size	5.1" x 3.47"	
Certification	ES, ETL, FCC, CE RoHS, TUV, ISO9001	
Operating Temperature	-20°C to 50°C (-4°F to 122°F)	
Environment	Indoor	
Warranty	3 years limited	

