

LPL



Vertical



Horizontal

TECHNICAL SPECIFICATIONS:

- :: Direct PL Lamp Replacement for fixtures with Electronic or Magnetic Ballasts
- :: Lumens: 800LM (9W) and 1200LM (12W)
- :: Magnetic-Ballast versions can also be connected to AC direct sockets with input voltage of 120~277V
- :: PF: 90% +
- :: CRI: >80
- :: Lifespan: 50,000 Hours, about 50 times the life of average fluorescent PL lamps
- :: Non-dimmable
- :: Operating Temp: -4~+113°F
- :: ETL listed

FEATURES:

- :: Long life—reduced re-lamping cost
- :: Contains No Mercury
- :: Emits no UV/IR light
- :: 5-year warranty









4-Pin only



C18

LED PL LAMPS

LED PL LAMPS

CATALOG NO.	BALLAST	POSITION	FLUORESCENT REPLACEMENT	ROTATABLE	WATTS	COLOR TEMP	LUMENS	BASE	
LPL-EB-9W-H-40K	Electronic	Horizontal	PL13	90°	9W	4000K	800LM		
LPL-EB-14W-H-L-40K	Electronic	Horizontal	PL18	90°	12W	4000K	1200LM		
LPL-EB-14W-V-40K	Electronic	Vertical	PL18	N/A	12W	4000K	1200LM		
LPL-MB-9W-H-40K	Magnetic or AC (Ballast override)	Horizontal	PL13	90°	9W	4000K	800LM		
LPL-MB-14W-H-L-40K	Magnetic or AC (Ballast override)	Horizontal	PL18	90°	12W	4000K	1200LM		
LPL-MB-14W-V-40K	Magnetic or AC (Ballast override)	Vertical	PL18	N/A	12W	4000K	1200LM		

