

JOB NAME:	
DATE:	





DIMENSIONS:

LSL-4FT-40W-35K-D LSL-4FT-40W-40K-D LSL-4FT-40W-50K-D LSL-2FT-20W-35K-D LSL-2FT-20W-40K-D LSL-2FT-20W-50K-D Models painted white
Wire guard kit available
for both sizes

LUMENS

4200LM

4200LM

4200LM

2200LM

2200LM

2200LM

COLOR TEMP

3500K

4000K

5000K

3500K

4000K

5000K

LED STRIP LIGHTS

LED Strip Light is a cost-effective, energy-efficient lighting fixture for surface mount application such as corridors, stairwells, public rooms, schools, hospitals utility areas, etc. Engineered with stable performance LED engines and world's top brand LED driver. Same footprint as traditional 2-lamp strip lights.

ELECTRICAL SPECIFICATIONS:

• Voltage: 120~277VAC 50/60Hz

· Wattages: 40W and 20W

Color Temperature: 3500K, 4000K and 5000K

• Operating Temperature: -4°F ~ 131°F

• Dimmable: 0~10V dimmable

• CRI: >80 • IP Rating: IP20

• Life span: 50,000 hrs.

HOUSING SPECIFICATIONS:

- · Housing: Steel base with powder coating
- · Lens: Frosted diffuse PC lens
- · Ceiling-mounted

WARRANTY:

5 years

CERTIFICATIONS:









LUX CHART:

MODEL

LSL-4FT-40W-35K-D


LSL-4FT-40W-40K-D

LSL-4FT-40W-50K-D

LSL-4FT-20W-35K-D

LSL-4FT-20W-40K-D

LSL-4FT-20W-50K-D



WATTS

40W

40W

40W

20W

20W

20W

VOLTS

120~277V

120~277V

120~277V

120~277V

120~277V

120~277V

Max , Ave Beam angle of C45plane116.12

PHOTOMETRICS:

