

JOB	NAME:	_
	DATE	

DIMENSIONS:

LSL-2FT-20W-35K-D LSL-2FT-20W-40K-D LSL-2FT-20W-50K-D LSL-2FT-20W-MCT-D

LED STRIP LIGHTS

LED Strip Light is a cost-effective, energy-efficient lighting fixture for surface mount application such as corridors, stairwells, public rooms, schools, hospitals utility areas, etc. Engineered with stable performance LED engines and world's top brand LED driver. Same footprint as traditional 2-lamp strip lights.

ELECTRICAL SPECIFICATIONS:

- Voltage: 120~277VAC 50/60Hz
- Wattages: 20W
- Color Temperature: 3500K, 4000K and 5000K
- Operating Temperature: -4°F ~ 131°F
- Dimmable: 0~10V dimmable
- CRI: >80
- IP Rating: IP20
- Life span: 50,000 hrs.

HOUSING SPECIFICATIONS:

- Housing: Steel base with powder coating
- Lens: Frosted diffuse PC lens
- Ceiling-mounted
- IP Rating: suitable for damp location

WARRANTY: 5 years

CERTIFICATIONS:




	MODEL	WATTS	VOLTS	LUMENS	COLOR TEMP
	LSL-2FT-20W-35K-D	20W	120~277V	2100LM	3500K
	LSL-2FT-20W-40K-D	20W	120~277V	2100LM	4000K
	LSL-2FT-20W-50K-D	20W	120~277V	2100LM	5000K
ĺ	LSL-2FT-20W-MCT-D	20W	120~277V	3500LM	МСТ

Models painted white Wire guard kit available

for both sizes

LUX CHART:



Max , Ave Beam angle of C45plane116.1?

PHOTOMETRICS:

