

JOB NAME: _____

DATE: _____

TYPE: _____

DIMENSIONS:

96"(L) x 3.4"(W) x 3.6"(H)



LSL-8FT-64W-50K-D LSL-8FT-64W-40K-D

LED STRIP LIGHT

Ideal for architectural lighting solutions, a variety of industrial, commercial and residential applications. Surface mount, wall mount or suspension mounting available.

ELECTRICAL SPECIFICATIONS:

- Voltage: 120-277VAC 50/60Hz
- Various ballast options available
- Wattage: 64W
- Power factor: >0.9

HOUSING SPECIFICATIONS:

- Evenly illuminated Frosted White polycarbonate lens
- Numerous knockouts for easy installation
- Easy wire way access
- Operating temperature: -22°F~104°F
- Lifespan: 50000 Hrs.
- IP rating: Dry Locations

CERTIFICATIONS: UL, DLC



MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP
LSL-8FT-64W-50K-D	64W	120~277V AC	7800lm	5000K
LSL-8FT-64W-40K-D	64W	120~277V AC	7800m	4000K

LIGHTING SPECIFICATIONS:

- Total lumens: 7800lm
- Color temperature: 4000K and 5000K
- Color rendering index: >80

WARRANTY: 5 years

