

PAR 38

LSPro LED PAR38 Lamp

Perfect Light Source for Commercial and Residential Applications



PRECISE LED BINNING PROCESS

Detailed and precise LED binning process for constant color output and temperature

90 CRI FOR EXCEPTIONAL COLOR

SPECIALIZED OPTIC DESIGN

Creates smooth, even light distribution.

EXPECT MORE FROM YOUR LED LIGHTING

The 17W/19W PAR38 LED lamp provides you with a crisp, beautifully lit environments, while requiring 80% less power and lasting 40 times longer than traditional incandescent bulbs. Perfect for a variety of commercial and residential applications, the PAR 38 is dimmable and provides a form easily utilized in a variety of luminaires.



PRECISE LED BINNING

Detailed and precise LED binning process for constant color output and temperature

SPECIALIZED OPTIC DESIGN

Creates smooth, even light distribution.

ENERGY STAR RATED

Energy Star rated for quality you can depend on





ORDERING INFORMATION

FAMILY	PRODUCT	WATTAGE EQUIVALENT	COLOR TEMPERATURE	DISTRIBUTION	VOLTAGE	PACKAGING
LSPRO	PAR38	90 WE - 90 WATT EQUIVALENT	W27 - SOFT WHITE 2700K	FL - FLOOD	120	BX - BOX
			WW - WARM WHITE 3000K	NFL - NARROW FLOOD		
			NW - NEUTRAL WHITE 4000K			
			CW - COOL WHITE 5000K			

example: LSPRO 38 90WE W27 FL 120 BX

PRODUCT NAME PAR38 90WE

SPECIFICATIONS	W27	WW	NW	CW
Color Temperature	2700K	3000K	4000K	5000K
Output (Lumens)	840	960	960	1020
Power Factor	.90	.90	.90	.90
CRI	90	90	90	90
Beam Angle	25° - Narrow Flood 40° - Flood			
Equivalent Source Standard	90 WE			
Input Voltage	120V			
Power Consumption	17W			
Dimmable	Yes			
Housing	Aluminum			
Base	E26			
Warranty	5 Year Limited			
Environment	Wet			
Certifications	Energy Star; RoHS; UL Listed			

1 Specifications and values supplied are nominal. Please refer to the DOE's Lighting Facts Tolerance Guidelines. Advances from further innovation and improvement continue and specifications are subject to change without notification.

2 Color temperatures conform to nominal CCTs as defined in ANSI Chromaticity Standard C78.377A

3 Lumen measurement complies with IES LM-79-08 testing procedures

4 Lumen maintenance calculations are based on measurements that comply with IES LM-80-08 testing procedures. L70 = 70% lumen maintenance, or when lamp reaches 70% of initial output

5 Please consult with Lighting Science Group for a list of compatible dimmers



ORDERING INFORMATION

FAMILY	PRODUCT	WATTAGE EQUIVALENT	COLOR TEMPERATURE	DISTRIBUTION	VOLTAGE	PACKAGING
LSPRO	PAR38	120 WE - 120 WATT EQUIVALENT	W27 - SOFT WHITE 2700K	FL - FLOOD	120	BX - BOX
			WW - WARM WHITE 3000K	NFL - NARROW FLOOD		
			NW - NEUTRAL WHITE 4000K			
			CW - COOL WHITE 5000K			

example: LSPRO 38 120WE W27 FL 120 BX

PRODUCT NAME PAR38 120WE

SPECIFICATIONS	W27	WW	NW	CW
Color Temperature	2700K	3000K	4000K	5000K
Output (Lumens)	1035	1200	1200	1300
Power Factor	.90	.90	.90	.90
CRI	90	90	90	90
Beam Angle	25° - Narrow Flood 40° - Flood			
Equivalent Source Standard	120 WE			
Input Voltage	120V			
Power Consumption	19W			
Dimmable	Yes			
Housing	Aluminum			
Base	E26			
Warranty	5 Year Limited			
Environment	Wet			
Certifications	Energy Star; RoHS; UL Listed			

1 Specifications and values supplied are nominal. Please refer to the DOE's Lighting Facts Tolerance Guidelines. Advances from further innovation and improvement continue and specifications are subject to change without notification.

2 Color temperatures conform to nominal CCTs as defined in ANSI Chromaticity Standard C78.377A

3 Lumen measurement complies with IES LM-79-08 testing procedures

4 Lumen maintenance calculations are based on measurements that comply with IES LM-80-08 testing procedures. L70 = 70% lumen maintenance, or when lamp reaches 70% of initial output

5 Please consult with Lighting Science Group for a list of compatible dimmers