

PROJECT NAME: _____ CATALOG NUMBER:

PRODUCT DESCRIPTION:

NOTES:

FIXTURE SCHEDULE:

Page: 1 of 1

WALL SCONCE

ML9 SERIES - BULB IN BOX

2700K



MaxLite

FEATURES:

- CRI: ≥90
- Flicker free bulb included (E26 Base) [Supports Compliance of JA8-2016-E]

LED Wall Sconces add long-lasting, energy-efficient illumination

with a decorative touch to corridors in homes, hotels, motels, and commercial property applications. The series is available in nickel, white, and dark bronze finish to complement virtually any interior style. This bulb in a box solution comes prepackaged with JA8 compliant LED bulbs for ease of installation and guarantee of high CRI, flicker free LED performance.

- Dedicated Voltage: 120V, 60Hz
- Five year limited warranty
- Triac dimming standard
- Operating Temperature: 0°F to 104°F

CONSTRUCTIONS:

- Formed Steel
- Powder coat finish
- High transmission lens

ORDERING*:

ORDER CODE	MODEL#	ITEM DESCRIPTION	
1408633	ML9E101CCNI27-V2	WALL SCONCE CONTEMPORARY NICKEL FINISH WITH 1x9W 2700K JA8 COMPLIANT E26 SOCKET LED LAMP	
1408634	ML9E101CCWH27-V2	WALL SCONCE CONTEMPORARY WHITE FINISH WITH 1x9W 2700K JA8 COMPLIANT E26 SOCKET LED LAMP	
1408635	ML9E101CCBZ27-V2	WALL SCONCE CONTEMPORARY DARK BRONZE FINISH WITH 1x9W 2700K JA8 COMPLIANT E26 SOCKET LED LAMP	

CDECIEICATIONS.

SPECIFICATIONS:		ML9E101CCNI27-V2	ML9E101CCWH27-V2	ML9E101CCBZ27-V2		
ITEM	SPECIFICATION					
GENERAL PERFORMANCE	Power Consumption (W)	9 (1 × 9)	9 (1 x 9)	9 (1 x 9)		
	Source Lumens	800	800	800		
	Efficacy (Im/W)	89	89	89		
	Color Temperature (K)	2700K				
	CRI	≥90				
	L70 Lumen Maintenance	25,000 hours				
ELECTRICAL	Input Voltage	120V				
	Input Frequency	60Hz				
	Power Factor	≥0.9				
PHYSICAL	Dimensions (L x W x H)	11" x 7.25" x 4.5"				
	Finish	Brushed Nickel, White, or Bronze				
	Operating Temperature	0°F to 104°F				
CERTIFICATION	Environment	Suitable for Damp Locations				
	Certification	Energy Star, ETL				
	Warranty	5 year limited warranty				