

## WALL SCONCE

### ML9 SERIES - LED INTEGRATED



### PRODUCT DESCRIPTION:

The LED Wall Sconce provides long-lasting illumination with a decorative touch to corridors in hotels, motels and commercial property applications. This integrated LED wall sconce solution offers long life, high lumen maintenance, and dimmable operation for residential and commercial applications that exceed those of a traditional bulb fixture.

### FEATURES:

- CRI ≥80 and flicker free
- Triac dimming
- Brushed nickel finish
- Dedicated voltage: 120V
- Suitable for damp locations
- 5 year warranty

### CONSTRUCTIONS:

- Die formed steel
- Powder coat
- Even light distribution



### ORDERING:

ORDER CODE	MODEL NUMBER	ITEM DESCRIPTION
14099634	ML9LAFBN09827	12" LED FLEMING WALL SCONCE 9W 80 CRI 2700K BRUSHED NICKEL

### SPECIFICATIONS:

#### ML9LAFBN09827

ITEM	SPECIFICATION	
GENERAL PERFORMANCE	Power Consumption (W)	9.7W
	Delivered Lumens	685 lm
	Efficacy (lm/W)	71.1 lm / W
	Color Temperature (K)	2700K (Additional CCT available, contact MaxLite for info.)
	CRI	≥80
	L70 Lumen Maintenance	50,000 hours
ELECTRICAL	Input Voltage	120V
	Input Frequency	60Hz
	Power Factor	≥0.9
	Compatible Dimmers	Leviton IPL06, Leviton SureSide 6674, Lutron LGCL-153P
PHYSICAL	Dimensions (L x W x H)	4.1"L x 5"W x 12"H
	Finish	Brushed Nickel
	Operating Temperature	-20°C to 40°C
CERTIFICATION	Environment	Suitable for Damp Locations
	Certification	ETL, FCC, Energy Star
	Warranty	5 year limited warranty