# LEDone


Projects:		
Comments:		

# PAR30 12W LED Bulbs Spec

### SPECIFICATIONS:

SPECIFICATIONS:		
WATTAGE:	12W	
MODEL #:	PAR30-60WE-12WD27K-B36	
UL & CUL:	E475740	
CERTIFICATIONS:	UL, CuL, FCC, CE, RoHS	
VOLTAGE:	120V	
POWER FACTOR:	>0.85	
FREQUENCY:	50/60 Hz	
LUMENS:	800LM	
LUMENS EFFICIENCY:	70.8 LM/W	
KELVIN (CCT):	2700	
THD:	>30%	
CRI:	85	
IP RATING:	IP20	
BEAM ANGLE (DEGREE):	36°	
BASE TYPE / CONNECTION:	E26	
LENS:	Frosted	
MATERIALS:	Aluminum Alloy + PC shell	
LED CHIPS:	COB LEDs	
POWER:	Internal	
LIFE SPAN (HOURS):	25000Hrs	
DIMMING COMPATIBLE:	Yes	
LENGTH OF WARRANTY (YEARS):	5 Years Standard	
PRODUCT LENGTH:	120.7mm	
PRODUCT DIAMETER:	90mm	
WORKING ENVIRONMENT:	-20°C - 40°C	
SUGGESTED REPLACEMENT FOR:	65WE	
POWER EFFICIENCY:	>90%	
PERCENTAGE OF WATTAGE SAVED:	45 - 50%	





### **Features:**

Energy efficient, up to 80% less energy than halogen alternatives. Exceed all industry performance requirements. Very durable: solid-state lighting technology significantly reduces lighting service and maintenance due to robust lighting design. Shatter resistant.

## **Applications:**

PAR30 are suitable for a variety of applications that require general area or directional lighting such as track lighting, recessed ceiling lights, retail display lighting or general household light fixtures.















