



Accessories:



RDL3-27K-WP RDL3-30K-WP RDL3-41K-WP RDL3-50K-WP

LED Trims (Smooth Trims) 3"

Isolated driver for improved thermal management.

ELECTRICAL SPECIFICATIONS:

- Voltage: 120V AC
- Wattage: 9W
- Power factor: 90% +

LIGHTING SPECIFICATIONS:

- LED type/brand: EPISTAR chip (COB)
- Driver-36,000-hour design life
- Dimmable: Yes
- Color temperature: 2700K and 3000K (Warm white), 4100K(Natural white), 5000K (Daylight)
- CRI: 90

OTHERS:

- Net weight: 0.76lbs / 345g
- Gross weight per CTN: 43.65lbs / 19.8kg

WARRANTY:

- Five-year warranty

MODEL NO	WATTS	LUMENS	VOLTAGE	COLOR TEMP
RDL3-27K-WP	9W	540LM	120V AC	2700K
RDL3-30K-WP	9W	540LM	120V AC	3000K
RDL3-41K-WP	9W	540LM	120V AC	4100K
RDL3-50K-WP	9W	540LM	120V AC	5000K

HOUSING SPECIFICATIONS:

- Housing: Spun aluminum with white powder coat finish
- Trim ring: Integrated spun aluminum white powder coat finish
- Gasket: Close cell Neoprene foam gasket
- Lens: 0.125" white translucent acrylic
- Wet locations: Suitable for damp locations
- Maximum ambient 4 °C (104 °F)
- Adjustable bracket can fit 5" and 6" housings

CERTIFICATIONS:

- UL listed
- Energy Star-rated (2700K, 3000K, and 4100K)
- Pending Energy Star-rated (5000K)

