LEDone®

PRODUCT DESCRIPTION:

Energy saving lamps and lanterns with high lumen, perfect color temperature and high CRI characteristics.

Application:


- Gas station lighting
- Petroleum canopies lighting
- CNG fueling stations lighting
- Low-medium bay general lighting

Soffits lighting

FEATURES:

- SMD LED chips
- Aluminum die-casting heat sinks for good heat dissipation
- No RF interference, no IR/UV radiation or mercury pollution

DIMENSIONS:





Page: 1 of 2

LED 150W Gas Station Light

RL-CP-150W-H3-M2-N-DW







SPECIFICATIONS:

Page: 2 of 2

SPECIFICATION	Details
Model	RL-CP-150W-H3-M2-N-DW
Input Wattage (W)	150W
Lumens Delivered (LM)	19,319.1LM
Efficacy (LM/W)	135.01LM/W
CRI	70
Lifespan	50,000 hours
Color Temperature	5,000K
Wattage Equivalent	500W
Dimmable	Available
Input Voltage	AC100-277V
Power Factor	0.9
Housing	Aluminum Alloy + PC shell
IP Rating	IP65
Lens	Frosted
THD	15%
Beam Angle	120 degree
Size and Weight (LBS)	21.65" X 21.65" X 1.18" 30.86lbs
Certification	DLC, ETL
Operating Temperature	-40 to 45 °C
Environment	Outdoor
Warranty	5 years

