

SL-P

80% DIM (OR OFF) WHEN NO MOTION DETECTED



SL-28W-BZ-P



SL-28W-WH-P



SL-20W-WH-P



SL-20W-WH-P



SL-30W-WH-P



SL-30W-WH-P

TECHNICAL SPECIFICATIONS:

- :: Westgate's dimming function security lights
- :: Mounts flush on wall or 4" round weatherproof box
- :: Housing: Die-cast aluminum with powder coat finish
- :: High-impact Polycarbonate lens
- :: CRI: 80
- :: Operating Temp: -40°F to 104°F
- :: Power factor: .90~.97
- :: Sensor angle: 180°
- :: Light beam angle: 120° (28W) - 100° (20W & 30W per head)
- :: Voltage: 120V AC 50/60Hz
- :: Suitable for Wet Locations, IP65
- :: 7-year warranty

Sensor Functions:

1. Always On: Set function lever to on-time. Lights always on; and can be controlled with a wall switch.
2. On with Motion Only: Set function lever to Auto. Lights turn on with motion detected from dusk to down. When object moves away, Lights turn off after 5s to 50min (Set with time dial)
3. On at 20% brightness from dusk to down with no motion detected: Set function lever to Dim. Lights turn on to full brightness when motion detected from dusk to down. When object moves away, Lights dim to 20% after 5s to 5min (Set with time dial)



LED SECURITY LIGHTS WITH PIR SENSOR

CATALOG NO.	FINISH	WATTS	LUMENS	COLOR TEMP	REPLACEMENT RANGE
SL-28W-50K-BZ-P	Bronze	28W	3400LM	5000K	100~150 MH
SL-28W-30K-BZ-P	Bronze	28W	3400LM	3000K	100~150 MH
SL-28W-50K-WH-P	White	28W	3400LM	5000K	100~150 MH
SL-28W-30K-WH-P	White	28W	3400LM	3000K	100~150 MH
SL-20W-50K-BZ-P	Bronze	20W	1900LM	5000K	70~100 MH
SL-20W-30K-BZ-P	Bronze	20W	1900LM	3000K	70~100 MH
SL-20W-50K-WH-P	White	20W	1900LM	5000K	70~100 MH
SL-20W-30K-WH-P	White	20W	1900LM	3000K	70~100 MH
SL-30W-50K-BZ-P	Bronze	30W	2800LM	5000K	100~150 MH
SL-30W-30K-BZ-P	Bronze	30W	2800LM	3000K	100~150 MH
SL-30W-50K-WH-P	White	30W	2800LM	5000K	100~150 MH
SL-30W-30K-WH-P	White	30W	2800LM	3000K	100~150 MH