

# FREE TO SHINE

# OFF-GRID LED SOLAR AREA LIGHT COMPARES TO 250W HID



- Off-Grid completely free to operate, plus notrenching or wiring required
- All-in-one design
- Exclusive long-lasting battery withstands extreme temperatures
- Easy to install and operate
- Adjustable solar panel multiple mounting and lens types available
- Slip-fitter bracket included with fixture
- Fixture Operating Temperature Range = -40F to 140F Battery Charging Temperature Range = -4F to 140F
- 3 year warranty on replaceable battery

## CE F©

PART #	UPC	COMPARABLE TO	LUMENS	сст	EPA
SL-SAL-OG-30W-50K-SF-BK-G1	844006049812	250W	5900	5000K	4.45

















solera-solar.com • 847.380.3540






### FREE TO SHINE


# **OFF-GRID**

LED SOLAR AREA LIGHT COMPARES TO 250W HID


### **Fixture Side View**



**Fixture Top View** 



(Total fixture weight = 30lbs)



#### ADDITIONAL BRACKETS MUST BE PURCHASED SEPARATELY (SLIP-FITTER BRACKET INCLUDED WITH FIXTURE)

REMPHOS PART # DESCRIPTION

SL-SAL-HYB-BKT-30W-RP-G1 Round pole bracket

SL-SAL-HYB-BKT-30W-SP-G1 Square pole bracket

SL-SAL-HYB-BKT-30W-TN-3-G1 3" square tenon bracket

SL-SAL-HYB-BKT-30W-RT-3-G1 3" round tenon bracket

SL-SAL-HYB-BKT-30W-WM-G1 Wall mount bracket











SL-SAL-HYB-BKT-30W-SP-G1

SL-SAL-HYB-BKT-30W-TN-3-G1

SL-SAL-HYB-BKT-30W-RT-3-G1

SL-SAL-HYB-BKT-30W-WM-G1

### Default Setting - No Adjustments Necessary

The default setting is Dusk 'till Dawn @ 80% first 2 hours, 50% constant & 80% w/ motion for the rest of the night.

