


JOB NAME:	
DATE: _	
TVDE.	

DIMENSIONS:

42"(L) x 1-1/2"(H) x 4"(D)





UCA-42-WHT UCA-42-BRZ

120-VOLT LED UNDERCABINET

Ideal for under cabinet, display cases, or in low-profile areas. UCA offers low heat, easy installation, environmentally friendly and maintenance free for many years.

ELECTRICAL SPECIFICATIONS:

Working Voltage: 120V (Internal Driver)

Wattage: 20 WEfficacy: 55 LM/W

HOUSING SPECIFICATIONS:

- Linkable
- 1/2" KOs for hardwiring installation (multiple on top and back)
- Built-in LED driver
- 22- gauge sheet metal housing, white/bronze enamel finish, painted after fabrication
- Very low, 1" profile, only 3-1/2" wide
- Tempered glass lens for easy cleaning inside frosted to reduce LED imaging
- 120V with plug and hardwire option included
- Color packaging with hanging tab
- 3/8" flex connector and mounting screws included
- Includes 6' power cord with plug and (1) 8" interconnect cable
- Key-holed mounting slots in housing simplify installation



6' Power Cord 8' interconnect cable End-to-End connector Mounting screws



On/Off Switch with 100%/50% Dimming Color Temp. Switch: 27000K/3000K/4000K



1/2" KOs Cable Connector Included

MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP
UCA-33-WHT	20W	120V	1100 LM	2700K/3000K/4000K
UCA-33-BRZ	20W	120V	1100 LM	2700K/3000K/4000K

LIGHTING SPECIFICATIONS:

- Lens: Tempered glass lens
- Total lumens: 1100 LM
- Adjustable color temperature(2700K/3000K/4000K)
- Color rendering index: 84

WARRANTY: 5 years

CERTIFICATIONS:

