



JOB NAME: _____

DATE: _____

TYPE: _____



- ULR-IN-16F-SO-27K
- ULR-IN-16F-SO-30K
- ULR-IN-16F-SO-40K
- ULR-IN-16F-SO-50K

24V INDOOR STANDARD OUTPUT LED RIBBON

Ideal for undercabinet, soffit, display cases and toe kick lighting.

ELECTRICAL SPECIFICATIONS:

- Voltage: 24VDC (LED driver required)
- Wattage: 1.5W per ft.
- Max Run: 49ft.
- Efficacy: 66LM/W per ft.

HOUSING SPECIFICATIONS:

- Cutting increment: Every 4 inches
- 3M double sided tape(9474LE) is preinstalled
- Includes 1 female ribbon-to-power supply connector (Prewired) and 1 male plug for connection to next ribbon (Prewired)
- IP rating: IP20

CERTIFICATIONS: UL



DIMENSIONS:

16.4'(L) x 0.31"(W)

| MODEL | WATTS PER FT. | VOLTAGE | LUMENS PER FT. | COLOR TEMP | REEL LENGTH | MAX RUN |
|-------------------|---------------|---------|----------------|------------|-------------|---------|
| ULR-IN-16F-SO-27K | 1.5W | 24VDC | 100LM | 2700K | 16.4FT. | 49FT. |
| ULR-IN-16F-SO-30K | 1.5W | 24VDC | 100LM | 3000K | 16.4FT. | 49FT. |
| ULR-IN-16F-SO-40K | 1.5W | 24VDC | 100LM | 4000K | 16.4FT. | 49FT. |
| ULR-IN-16F-SO-50K | 1.5W | 24VDC | 100LM | 5000K | 16.4FT. | 49FT. |

OPTIONAL ACCESSORIES:



ULR-IN-SO-COUP-6I-WR
ULR-IN-SO-COUP-3F-WR



ULR-IN-SO-COUP-NO-WR



ULR-IN-SO-CONN-6I-WR
ULR-IN-SO-CONN-3F-WR

| MODEL | DESCRIPTION |
|----------------------|---|
| ULR-IN-SO-COUP-6I-WR | Coupling to connect 2 standard output ribbons, 6" |
| ULR-IN-SO-COUP-3F-WR | Coupling to connect 2 standard output ribbons, 3' |
| ULR-IN-SO-COUP-NO-WR | Coupling to connect 2 standard output ribbons, no wire |
| ULR-IN-SO-CONN-6I-WR | Power feed cable to connect standard output ribbon to power, 6' |
| ULR-IN-SO-CONN-3F-WR | Power feed cable to connect standard output ribbon to power, 3' |

LIGHTING SPECIFICATIONS:

- Dimming: Dimmable using a magnetic driver
- LED: SMD2216 chip spaced 5/8" on center, 19 per foot, 0.08 wats each chip
- LED Type: SMD2216
- Total lumens: 100LM per ft.
- Color temperature: 2700K/3000K/4000K/5000K
- Color rendering index: 80
- Beam Angle: 120°

WARRANTY: 5 years

