



JOB NAME: \_\_\_\_\_

DATE: \_\_\_\_\_

TYPE: \_\_\_\_\_



- ULR-IN-16F-XHO-27K
- ULR-IN-16F-XHO-30K
- ULR-IN-16F-XHO-40K
- ULR-IN-16F-XHO-50K

## 24V INDOOR EXTRA HIGH OUTPUT LED RIBBON

Ideal for undercabinet, soffit, display cases and toe kick lighting.

### ELECTRICAL SPECIFICATIONS:

- Voltage: 24VDC (LED driver required)
- Wattage: 8.8W per ft.
- Max Run: 11ft.
- Efficacy: 70~79LM/W per ft.

### HOUSING SPECIFICATIONS:

- Cutting increment: Every 2 inches
- 3M double sided tape(9474LE) is preinstalled
- Includes 1 female ribbon-to-power supply connector (Prewired) and 1 male plug for connection to next ribbon (Prewired)
- IP rating: IP20

### CERTIFICATIONS: UL



### DIMENSIONS:

16.4'(L) x 0.4"(W)

MODEL	WATTS PER FT.	VOLTAGE	LUMENS PER FT.	COLOR TEMP	REEL LENGTH	MAX RUN
ULR-IN-16F-XHO-27K	8.8W	24VDC	620LM	2700K	16.4FT.	11FT.
ULR-IN-16F-XHO-30K	8.8W	24VDC	620LM	3000K	16.4FT.	11FT.
ULR-IN-16F-XHO-40K	8.8W	24VDC	680LM	4000K	16.4FT.	11FT.
ULR-IN-16F-XHO-50K	8.8W	24VDC	700LM	5000K	16.4FT.	11FT.

### OPTIONAL ACCESSORIES:



ULR-IN-HO-COUP-6I-WR  
ULR-IN-HO-COUP-3F-WR



ULR-IN-HO-COUP-NO-WR



ULR-IN-HO-CONN-6I-WR  
ULR-IN-HO-CONN-3F-WR

MODEL	DESCRIPTION
ULR-IN-HO-COUP-6I-WR	Coupling to connect 2 Extra high output ribbons, 6"
ULR-IN-HO-COUP-3F-WR	Coupling to connect 2 Extra high output ribbons, 3'
ULR-IN-HO-COUP-NO-WR	Coupling to connect 2 Extra high output ribbons, no wire
ULR-IN-HO-CONN-6I-WR	Power feed cable to connect Extra high output ribbon to power, 6"
ULR-IN-HO-CONN-3F-WR	Power feed cable to connect Extra high output ribbon to power, 3'

### LIGHTING SPECIFICATIONS:

- Dimming: Dimmable using a magnetic driver
- LED: SMD2835 chip spaced 1/3" on center, 37 per foot, 0.23 wats each chip
- LED Type: SMD2835
- Total lumens: 620~700LM per ft.
- Color temperature: 2700K/3000K/4000K/5000K
- Color rendering index: 80
- Beam Angle: 120°

### WARRANTY: 5 years

