

PRODUCT DESCRIPTION:

T8 linear tube retrofits are usually but not specifically used in commercial buildings such as hotels, conference rooms, schools, supermarkets, factory, parking garages, hospitals, airport, metro stations, bus stations, office buildings and any other sites where request long-time and hi-output lighting.

FEATURES:

- Input voltage is AC110V-277V
- Low thermal decay
- Low maintenance
- No mercury, lead-free
- No UV

COMPATIBLE BALLAST LIST:

- For compatible ballasts, please check on the website under the Tube section > Plug & Play LED Tube > Ballast List

Plug & Play Tube 4FT 22W Spec

LOD-C08-M1218(4000K)

LOD-C08-M1218(5000K)



SPECIFICATIONS:

SPECIFICATION	Details	
Model	LOD-C08-M1218(4000K)	LOD-C08-M1218(5000K)
Input Wattage (W)	22W	22W
Lumens Delivered (LM)	2,488.73LM	2,617.2LM
Efficacy (LM/W)	112.61LM/W	117.89LM/W
CRI	82	83.1
Lifespan	50,000 hours	50,000 hours
Color Temperature	4,000K	5,000K
Wattage Equivalent	32W – 36W	32W – 36W
Dimmable	No	No
IP Rating	IP40	IP40
Beam Angle	120	120
Input Voltage	AC110-277V	AC110-277V
Power Factor	0.95	0.96
Housing	Aluminum	Aluminum
Lens	Frosted	Frosted
Mounting	G13	G13
Size	48"	48"
Weight (LBS)		
Certification	DLC, UL, FCC, CE RoHS, TUV, ISO9001	DLC, UL, FCC, CE RoHS, TUV, ISO9001
Operating Temperature	-20°C to 50°C (-4°F to 122°F)	-20°C to 50°C (-4°F to 122°F)
Environment	Indoor	Indoor
Warranty	5 years limited	5 years limited

