

PRODUCT DESCRIPTION:

T8 linear tube retrofits are usually but not specifically used in commercial buildings such as hotels, conference rooms, schools, supermarkets, factory, parking garages, hospitals, airport, metro stations, bus stations, office buildings and any other sites where request long-time and hi-output lighting.

FEATURES:

- Type B Single or Double Ended
- Plug & Play Dual Mode (type A & B)
- Shatterproof glass
- Input voltage is AC110V-277V
- Low thermal decay
- Low maintenance
- No mercury, lead-free
- No UV

COMPATIBLE BALLAST LIST:

- For compatible ballasts, please check on the website under the Tube section > Plug & Play LED Glass Shatterproof > Ballast List

Shatterproof Proof Tube 4FT 17W Spec

LOD-GDMT84F-17W40KF YM

LOD-GDMT84F-17W50KF YM



SPECIFICATIONS:

SPECIFICATION	Details	
Model	LOD-GDMT84F-17W40KF YM	LOD-GDMT84F-17W50KF YM
Input Wattage (W)	17W	17W
Lumens Delivered (LM)	2,300LM	2,300LM
Efficacy (LM/W)	136LM/W	136LM/W
CRI	80	80
Lifespan	50,000 hours	50,000 hours
Color Temperature	4,000K	5,000K
Wattage Equivalent	32W – 36W	32W – 36W
Dimmable	No	No
IP Rating	IP40	IP40
Beam Angle	270	270
Input Voltage	AC110-277V	AC110-277V
Power Factor	0.9	0.9
Housing	Glass	Glass
Lens	Frosted	Frosted
Mounting	G13	G13
Size	48"	48"
Weight (LBS)		
Certification	DLC, UL, FCC, CE RoHS, TUV, ISO9001	DLC, UL, FCC, CE RoHS, TUV, ISO9001
Operating Temperature	-20°C to 50°C (-4°F to 122°F)	-20°C to 50°C (-4°F to 122°F)
Environment	Indoor	Indoor
Warranty	5 years limited	5 years limited

