



Application: Commercial; Retail; school/institution; government agency; grocery store....



Specification		
Model No.	HY-T8-18P4FT-BXXK	HY-T8-20P4FT-BXXK
Power:	18W	20W
Input Voltage:	AC100-277V	
Luminous Flux:	2,340 LM	2,600 LM
Power Factor:	>0.9	
THD:	<10%	
CCT:	4000K/5000K/6500K	
Cover:	Clear/Frosted	
DLC Family ID	NANPLM	NANPLN
CRI:	>80	
Working Life:	>50,000 hours	
Working Temperature:	4°F to 105°F	

GENERAL DESCRIPTION

The T8 LED Tube bring the energy saving capabilities of LED technology to the commercial environment. And this T8 LED Tube can be done easily with a ballast bypass (direct wire) installation.

FEATURES

- Available in clear, frosted PC cover
- Aluminum housing and high purity aluminum materials with anodic oxidation process
- High energy efficiency: save more than 60% energy versus fluorescent lamps
- Ballast Bypass: Wire to mains for easy and quick installation and eliminate ballast maintenance cost

Ordering Guide

Model No: HY-T8 -XXP4FT-B(XX)K-X						
Company Code	Size	Watt	Length	Wiring Type	C.C.T.	Cover
HY	T8: T8 Tube	18P: 18 watt 20P: 20 watt	4FT	B: Type B- Bypass	4000K 5000K 6500K	T: Transparent Cover F: Frosted Cover